

Poynting MIMO-3-12, Ultra-Wideband, 2-in-1 Automotive, 2x2 MIMO 4G-5G antenna; 410 to 3800 MHz

SKU: ANT-PY-00010

MPN: A-MIMO-0003-V2-12

Description

The Poynting MIMO-3-12 is a versatile, ultra-wideband 2x2 MIMO antenna designed for automotive applications, supporting 4G and 5G networks across a broad frequency range of 410 to 3800 MHz. With its robust ASA plastic construction and IP68 rating, this antenna is built to withstand harsh environmental conditions, making it ideal for outdoor use. It operates efficiently in temperatures from -40 °C to 80 °C, ensuring reliable performance in various climates.

This fin-style antenna features two input ports, each equipped with an SMA Male connector and 2000 mm cable, facilitating seamless integration into existing systems. The antenna's linear polarisation and 50 Ω impedance optimise signal transmission, supporting up to 10 W of input power. Its peak gain ranges from 1.0 dBi to 5.8 dBi across different frequency bands, ensuring enhanced signal reception and transmission quality.

Poynting, a leading provider of integrated antenna solutions...

[Read More](#)



Poynting

Poynting is a top global provider of integrated antenna solutions, responsible for the innovation, design and manufacture of its market-leading products. Established as a consultancy in 1990, Poynting evolved into an official PTY in 1997 and in 2001 established Poynting Antennas. It caters antenna solutions for primarily wireless high speed data applications, including residential 4G LTE as well ...

RF Specification

Cable 1: 4G-5G

Start Frequency:	410 MHz	Polarisation:	Linear
Stop Frequency:	3800 MHz	Input Impedance:	50
Max. Input Power:	10 W		

RF Connectors

Ports	RF Interface	Body Shape	Length
1	SMA Male	Straight	2000 mm

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR
410 MHz	470 MHz	1 dBi	< 2.5:1
690 MHz	960 MHz	3.5 dBi	< 2.5:1
1710 MHz	2700 MHz	5.8 dBi	< 2.5:1
3400 MHz	3800 MHz	4 dBi	< 2.5:1

Cable 2: 4G-5G

Start Frequency:	410 MHz	Polarisation:	Linear
Stop Frequency:	3800 MHz	Input Impedance:	50
Max. Input Power:	10 W		

RF Connectors

Ports	RF Interface	Body Shape	Length
1	SMA Male	Straight	2000 mm

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR
410 MHz	470 MHz	1 dBi	< 2.5:1
690 MHz	960 MHz	3.5 dBi	< 2.5:1
1710 MHz	2700 MHz	5.8 dBi	< 2.5:1
3400 MHz	3800 MHz	4 dBi	< 2.5:1

Physical Specification

Subtype:	Fin / Stud / Combo	Dimensions:	253 x 128 x 144
Input Ports:	2	Ingress Protection:	IP68
MIMO:	2x2 MIMO	Materials:	ASA Plastic
Min. Operating Temperature:	-40 °C	Weight:	1.1 kg
Max. Operating Temperature:	80 °C	Compliance/Certifications:	CE
		RoHS	
		ISO 9001 Quality Management	
		Mechanical Compliance:	MIL-STD-810: Environmental Durability

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

