

# Blackhawk 4G Trucker Edge Antenna, 698 to 2200 MHz, SMA Male

SKU: ANT-BH-OM-202TB-2

MPN: VVCL-6922-6.SA1B

Barcode: 9337692000423

## Description

The Blackhawk 4G Trucker Edge Antenna (SKU: ANT-BH-OM-202TB-2) provides good performance across a frequency range of 698 to 2200 MHz, making it an ideal solution for enhancing cellular 4G-5G mobile network coverage. This vehicle antenna is designed with rugged materials, including fibreglass (GRP), stainless steel, and aluminium, ensuring durability in diverse environments from -40 °C to 65 °C.

Featuring a single SMA Male input port, this vertical polarised antenna supports a 50 Ω impedance and can handle up to 50 W of input power. It provides consistent RF performance with peak gains ranging from 5.3 to 5.8 dBi and low VSWR values across its operating bands, ensuring efficient signal transmission. The antenna's omnidirectional azimuth beamwidth of 360° ensures consistent coverage.

Measuring 950 x 60 mm and weighing 1.8 kg, the antenna is both compact and durable, facilitating easy installation on vehicles or fixed locations. The attached...

[Read More](#)



## Blackhawk Antennas

Blackhawk Antennas are a quality antenna supplier based in Australia. Primarily supplying equipment to improve cellular mobile network performance, Blackhawk equipment represents a best-in-class solution which carefully balances economics with RF performance. Blackhawk Antennas supply premium grade mobile bandwidth suitable (3G, 4G, 4GX, 5G), quality tested, ruggedised antennas ideal for all types ...

# RF Specification

Start Frequency:	698 MHz	Polarisation:	Vertical (V)
Stop Frequency:	2200 MHz	Input Impedance:	50
Max. Input Power:	50 W		

## RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	SMA Male	Straight	L-240	4500 mm

## Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR	Azimuth	Elevation
698 MHz	803 MHz	5.4 dBi	< 2.3:1	360°	48°
803 MHz	890 MHz	5.8 dBi	< 1.5:1	360°	44°
890 MHz	960 MHz	5.3 dBi	< 1.5:1	360°	49°
1695 MHz	1880 MHz	5.6 dBi	< 1.7:1	360°	60°
1880 MHz	2200 MHz	5.5 dBi	< 1.7:1	360°	65°

# Physical Specification

Subtype:	Collinear	Dimensions:	950 x 60
Input Ports:	1	Materials:	Aluminium, Fibreglass (GRP), Stainless Steel (304)
MIMO:	1x1 SISO	Weight:	1.8 kg
Min. Operating Temperature:	-40 °C	Compliance/Certifications:	ISO 9001 Quality Management
Max. Operating Temperature:	65 °C	RoHS	,

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

