

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

2J Blade 4G-5G WiFi Ultraband Hinged Antenna, 617 to 5925 MHz, SMA Male

SKU: ANT-2J-00001 MPN: 2JW1183-C952B

Description

Introducing the 2J Blade 4G-5G WiFi Ultraband Hinged Antenna (SKU: ANT-2J-00001), designed for robust performance across a wide frequency range from 617 MHz to 5925 MHz. Engineered with precision, this hinged terminal antenna features a compact design measuring 135 x 19 x 10 mm and is constructed from durable polycarbonate and ABS plastic. It operates effectively in harsh environments with a temperature range of -40 °C to 85 °C.

The antenna supports one SMA Male RF connection and delivers reliable performance with a 50 Ω impedance, handling up to 25 W input power.

Performance metrics include a peak gain of -1.1 dBi and radiated efficiency of 38% for 617-960 MHz, a peak gain of 0.5 dBi and 43% efficiency for 1427-2690 MHz, and a peak gain of 1.6 dBi with 42% efficiency for 5150-5925 MHz. The antenna is RoHS compliant, ensuring adherence to environmental standards.

2J, a trusted name in the industry, offers advanced antenna solutions for...

Read More

2J

12J

2J is a worldwide supplier of antenna solutions for Automotive, Marine, Telematic, Automation and M2M markets. 2J utilise a plethora of modern engineering tools, from network analysers and anechoic chambers, to simulation software and 3D printers. These tools help reduce design phases, and enable us to react to customers' needs promptly and efficiently.

Over the past decade, 2J has established ...



RF Specification

Start Frequency:	617 MHz	Polarisation:	Linear
Stop Frequency:	5925 MHz	Input Impedance:	50
Max. Input Power:	25 W		

RF Connectors

RF Interface	Body Shape
SMA Male	Straight

Frequency Test Data

617 MHz 960 MHz -1.1 dBi > 11.2 dB < 2:1	Start Freq.	Stop Freq.	Peak Gain	Return Loss	VSWR	Azimuth	Avg. Gain	Efficiency
1427 MHz 2690 MHz 0.5 dBi > 10.7 dB < 2.6:1 360° -3.8 dBi 43% 3300 MHz 5000 MHz 0.3 dBi > 11.4 dB < 2.3:1	617 MHz	960 MHz	-1.1 dBi	> 11.2 dB	< 2:1	360°	-4.3 dBi	38%
3300 MHz 5000 MHz 0.3 dBi > 11.4 dB < 2.3:1 360° -4.6 dBi 35%	1427 MHz	2690 MHz	0.5 dBi	> 10.7 dB	< 2.6:1	360°	-3.8 dBi	43%
	3300 MHz	5000 MHz	0.3 dBi	> 11.4 dB	< 2.3:1	360°	-4.6 dBi	35%
5150 MHZ 5925 MHZ 1.6 dBI > 8.8 dB < 2.1:1 360° -3.8 dBI 42%	5150 MHz	5925 MHz	1.6 dBi	> 8.8 dB	< 2.1:1	360°	-3.8 dBi	42%

Physical Specification

Subtype:	Hinged Terminal	Dimensions:	135 x 19 x 10
Input Ports:	1	Materials:	ABS Plastic, Polycarbonate (PC)
MIMO:	1x1 SISO	Mounting:	Terminal / Device
Min. Operating Temperature:	-40 °C	Compliance/Certifications:	RoHS
Max. Operating Temperature:	85 °C		

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

