

# Huang Liang BMA Female to SMA Female 2-Hole Flange Mount Adapter

SKU: ACC-HL-00062

MPN: 160-A610.118

## Description

The Huang Liang BMA Female to SMA Female 2-Hole Flange Mount Adapter (Part Number: 160-A610.118) is a high-quality 50 Ω coaxial RF adapter. This adapter features a BMA Female interface with a straight body and 2-hole flange front mount, compatible with BMA Male interfaces. The SMA Female interface also has a straight body and 2-hole flange rear mount, compatible with SMA Male interfaces.

Operating within a frequency range of 0 GHz to 18 GHz, this adapter is suitable for various applications, including military, telecommunications, and aerospace. Constructed from stainless steel (303) with a passivated finish, it ensures durability and corrosion resistance. The inner contacts are made from beryllium copper with gold plating, enhancing signal integrity and reliability.

Designed to perform in extreme conditions, it operates between -65 °C and 125 °C. Huang Liang ensures compliance with ISO 9001 Quality Management and RoHS standards...

[Read More](#)



## Huang Liang



Huang Liang is a Taiwanese manufacturer of precision coaxial connectors, adapters and cable assemblies. The company provide solutions to different industries including military, telecommunications, and aerospace.

Over 30 years of experience in developing and designing RF products, Huang Liang has overcome many challenges, resulting in unmatched expertise in the field of RF technology. Huang Liang ...

# RF Connector Interface

RF Interface	Body Shape	Mounting
BMA Female	Straight	2-Hole Flange
SMA Female	Straight	2-Hole Flange

## RF Specification

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	18 GHz	Inner Contact Resistance:	$\leq 6 \text{ m}\Omega$
RF Operating Voltage:	$\geq 375 \text{ Vrms}$	Insulation Resistance:	$\geq 5000 \text{ m}\Omega$
		Outer Contact Resistance:	$\leq 2 \text{ m}\Omega$


## VSWR Measurement

Frequency	VSWR	Insertion Loss
18000 MHz	$\leq 1.3:1$	0.25 dB

## Physical Specification

Body Material:	Stainless Steel (303)	Contact Material:	Beryllium Copper
Body Plating:	Passivated	Contact Plating:	Gold
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-65 °C
Compliance/Certifications:	ISO 9001 Quality Management	Max. Operating Temperature:	125 °C
RoHS		Mating Cycles:	> 500

# Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

