

# Panorama Wall Mount 4G-5G MIMO Gain Antenna, 5m SMA Male

SKU: ANT-PA-00016

MPN: WMM8G-7-38-5SP

## Description

The Panorama Wall Mount 4G-5G MIMO Gain Antenna (SKU: ANT-PA-00016) by Panorama Antennas is designed for robust and high-performance communication in modern networks. This panel antenna, model WMM8G-7-38-5SP, offers excellent coverage across 698 MHz to 3800 MHz frequency ranges. Featuring 2x2 MIMO capabilities, it ensures enhanced data throughput and reliable signal reception, ideal for critical communication, M2M, IoT, and in-building applications.

Constructed with durable ASA Plastic and certified with an IP65 ingress protection rating, this antenna is built to withstand harsh environmental conditions, operating efficiently between temperatures of -45 °C to 80 °C. It features two input ports with SMA Male connectors attached to a 5m RG-58 cable, facilitating easy integration into various setups.

The antenna delivers peak gains of up to 9.0 dBi, ensuring strong signal strength and stable connectivity. With a slant +45° polarisation, it...

[Read More](#)



### Panorama Antennas

Panorama's constant cutting-edge research ensures that our antennas meet the demands of the very latest communication technologies. Trusted by thousands of professionals and consumers the world over, our antennas are depended upon to provide communications even in the most challenging conditions.

Currently, Panorama specialises in professional antenna solutions for modern communications ...

# RF Specification

## Cable 1: 4G-5G

Start Frequency:	698 MHz	Polarisation:	Slant +45°
Stop Frequency:	3800 MHz	Input Impedance:	50
Max. Input Power:	20 W		

## RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	SMA Male	Straight	RG-58	5000 mm

## Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR
698 MHz	960 MHz	6 dBi	< 2:1
1710 MHz	2700 MHz	9 dBi	< 2:1
3400 MHz	3800 MHz	9 dBi	< 2:1

# Physical Specification

Subtype:	Panel / Sector	Dimensions:	180 x 200 x 94
Input Ports:	2	Ingress Protection:	IP65
MIMO:	2x2 MIMO	Materials:	ASA Plastic
Min. Operating Temperature:	-45 °C	Weight:	0.96 kg
Max. Operating Temperature:	80 °C		

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

