

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

# PTL-100 Patch Cable TS9 to SMA Female 18cm (suit Nighthawk)

SKU: ACC-PT-00144

MPN: CA-100-TS9SA2.018 Barcode: 9337692002489


#### Description

The PTL-100 Patch Cable, model CA-100-TS9SA2.018, by Powertec is a high-quality RF cable designed for connecting TS9 to SMA Female interfaces, ideal for modems like the Netgear Nighthawk. This 18 cm cable is crafted with L-100 coaxial, a superior alternative to RG-174 and RG-316, offering exceptional RF shielding of over 90 dB. Its design supports high-frequency microwave applications up to 63 GHz, though typically used below 6 GHz.

The TS9 connector is specifically suited for 4G modems requiring 2x2 MIMO configurations, providing enhanced performance by allowing the connection of larger antennas. It's important to note the incompatibility between TS9 and CRC9 connectors, the latter used by brands like Huawei and ZTE.

This patch cable is lightweight at 53 grams and durable, capable of over 50 mating cycles. It operates within a frequency range of 0 to 6 GHz and complies with ISO 9001 and RoHS standards. Performance-wise, it boasts a VSWR...

Read More





#### Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

# **RF** Specification


Start Frequency:	0 GHz	Stop Frequency:	6 GHz	
VSWR Measure	ment			
	Frequency		VSWR	
	3000 MHz		≤ 1.2:1	
	6000 MHz		≤ 1.5:1	

# **Physical Specification**

Subtype:	Patch Cable	Length:	0.18 m	
Mating Cycles:	> 50	Weight:	53 g	
Compliance/Certifications:	ISO 9001 Quality Management			
RoHS	,			

#### **RF Connectors**

RF Interface	Body Shape	Mounting
TS-9 Male	Straight	Free Hanging



### L-100

Min. Frequency:	0 GHz	Max. Frequency:	63 GHz
Impedance:	50	Shielding Effectiveness:	> 90 dB
Min. Bend Radius Static:	6.4 mm	Colour:	Black
Min. Bend Radius Dynamic:	25.4 mm		
Attenuation @ 1 GHz:	0.78 dB/m		

## Cable Layers

Layer	Diameter	Materials
Inner Conductor	0.46 mm	Solid Copper
Dielectric	1.52 mm	Polyethylene (PE)
Outer Conductor	1.65 mm	Aluminium Foil
Outer Conductor	2.11 mm	Tinned Copper Braid (TC)
Outer Jacket	2.79 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

