

Panorama LPB-6-60 Low Profile 4G-5G Antenna, N Female

SKU: ANT-PA-00102
 MPN: LPB-6-60-NJ

Description

The Panorama LPB-6-60 Low Profile Antenna is designed for efficient 4G and 5G connectivity, making it ideal for both industrial and domestic applications. Its robust design supports a wide frequency range from 617 MHz to 6000 MHz, ensuring reliable communication across multiple bands. This antenna is particularly suitable for environments utilising cellular modems, routers, and machine-to-machine (M2M) applications, where stable and high-speed wireless communication is essential.

Constructed from durable ASA plastic and aluminium, the LPB-6-60 ensures longevity and performance in harsh conditions, with an operating temperature range of -40 °C to 85 °C and an IP66 ingress protection rating. This makes it well-suited for outdoor installations where exposure to dust and water is a concern.

The antenna's vertical polarisation and 360° azimuth provide optimal signal coverage, while its peak gain of up to 9.0 dBi enhances signal strength. The...

[Read More](#)



RF Specification

Start Frequency:	617 MHz	Polarisation:	Vertical (V)
Stop Frequency:	6000 MHz	Input Impedance:	50
Max. Input Power:	30W	Panorama's constant cutting-edge research ensures that our antennas meet the demands of the very latest communication technologies. Trusted by thousands of professionals and consumers the world over, our antennas are provided upon to provide communications even in the most challenging conditions.	
RF Connectors		Currently, Panorama specialises in professional antenna solutions for modern communications ...	

Ports	RF Interface	Body Shape	Cable Series	Length
1	N Female	Straight	RG-58	2000 mm

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR	Azimuth	Efficiency
617 MHz	960 MHz	3 dBi	< 2.5:1	360°	70%
1710 MHz	2700 MHz	4 dBi	< 2.5:1	360°	70%
3400 MHz	3800 MHz	8 dBi	< 2.5:1	360°	70%
4900 MHz	6000 MHz	9 dBi	< 2.5:1	360°	70%

Physical Specification

Subtype:	Panel / Sector	Dimensions:	82 x 48 (H x Dia)
Input Ports:	1	Ingress Protection:	IP66
MIMO:	1x1 SISO	Materials:	ASA Plastic, Aluminium
Min. Operating Temperature:	-40 °C	Mounting:	Stud / Bulkhead / Panel
Max. Operating Temperature:	85 °C	Weight:	0.25 kg
		Compliance/Certifications:	CE
		Mechanical Compliance:	IEC 60529: IP Code

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

