

Panorama 4G-5G 2x2 MIMO, Sharkfin Antenna with External VHF Whip Port, 617 to 6000 MHz

SKU: ANT-PA-00107

MPN: GPSD-6-60

Description

The Panorama 4G-5G 2x2 MIMO Sharkfin Antenna with External VHF Whip Port is a versatile antenna solution designed for enhanced connectivity across a broad frequency range of 617 to 6000 MHz. Its primary application is in providing robust and reliable cellular communication for both 4G and 5G networks, making it ideal for various industrial, transport, and public safety applications where consistent connectivity is crucial. The inclusion of a 2x2 MIMO configuration facilitates improved data throughput and network reliability, which is particularly beneficial in high-density environments.

The antenna is equipped with an external VHF whip port, allowing for additional customisation and application-specific enhancements. Its durable construction, featuring ASA plastic and aluminium, ensures resilience in harsh conditions, while its IP69K ingress protection rating guarantees protection against dust and high-pressure water jets, making it...

[Read More](#)



Panorama Antennas

Panorama's constant cutting-edge research ensures that our antennas meet the demands of the very latest communication technologies. Trusted by thousands of professionals and consumers the world over, our antennas are depended upon to provide communications even in the most challenging conditions.

Currently, Panorama specialises in professional antenna solutions for modern communications ...

RF Specification

Cellular

Start Frequency:	617 MHz	Polarisation:	Vertical (V)
Stop Frequency:	6000 MHz	Input Impedance:	50

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	SMA Male	Straight	RG-174	300 mm

GPS/GLONASS/Galileo/BeiDou

Start Frequency:	1562 MHz	Input Impedance:	50
Stop Frequency:	1612 MHz	Polarisation:	Right Hand Circular (RHCP)

Low Noise Amplifier (LNA)

LNA Gain:	26 dBic	Min. Operating Voltage:	3 V
		Max. Operating Voltage:	5 V

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	FME Female	Straight	RG-174	300 mm

Physical Specification

Subtype:	Fin / Stud / Combo	Dimensions:	90 x 243 x 63 (H x L x W mm)
Input Ports:	2	Ingress Protection:	IP69K
MIMO:	2x2 MIMO	Materials:	ASA Plastic, Aluminium
Min. Operating Temperature:	-40 °C	Mounting:	Stud / Bulkhead / Panel
Max. Operating Temperature:	80 °C	Compliance/Certifications:	RoHS

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

