

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Poynting HELI-21, Circular-Polarised Tunnel, Dual Band WiFi antenna; 2400 to 6000 MHz

SKU
ANT-PY-00028
MPN
A-HELI-0021-V3-01

Description

The Poynting HELI-21 is a robust circular-polarised dual-band WiFi antenna, ideal for demanding environments such as tunnels. Covering a frequency range from 2400 to 6000 MHz, it provides reliable connectivity across various applications, including 4G LTE, GSM, M2M, and DTV. With a helical design, the HELI-21 supports 2x2 MIMO technology, enhancing wireless performance.

Constructed from durable ABS plastic and PVC, the antenna is IP65 rated, ensuring resistance to dust and water ingress, and operates effectively in extreme temperatures from -40 °C to 70 °C. This makes it a reliable choice for outdoor and industrial applications. It features four RF connections with 50 Ω impedance, supporting up to 30 W input power, and is LHCP polarised for improved signal clarity.

The HELI-21 offers impressive RF performance with peak gains of 12.0 dBi and 13.0 dBi in its respective frequency ranges, maintaining a VSWR of less than 1.5:1. It includes an...

[Read More](#)



[Poynting](#)

Poynting is a top global provider of integrated antenna solutions, responsible for the innovation, design and manufacture of its market-leading products.

Established as a consultancy in 1990, Poynting evolved into an official PTY in 1997 and in 2001 established Poynting Antennas. It caters antenna solutions for primarily wireless high speed data applications, including residential 4G LTE as well ...

RF Specification

Port 1

Start Frequency

2400 MHz

Stop Frequency

6000 MHz

Max. Input Power

30 W

Polarisation

[Left Hand Circular \(LHCP\)](#)

Input Impedance

50 Ω

RF Connectors

Ports RF Interface Body Shape Cable Series Length

1 [N Male](#) [Straight](#) [RG-58](#) 350 mm

Frequency Test Data

Start Freq. Stop Freq. Peak Gain VSWR

2400 MHz 2500 MHz 12 dBi < 1.5:1

5000 MHz 6000 MHz 13 dBi < 1.5:1

Physical Specification

Subtype

[Helical](#)

Input Ports

4

MIMO

[2x2 MIMO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

70 °C

Dimensions

526 x 415 x 266

Ingress Protection

[IP65](#)

Materials

[ABS Plastic, Polyvinyl Chloride \(PVC\)](#)

Weight

3.9 kg

Compliance/Certifications

CE

,

RoHS

,

ISO 9001 Quality Management

Mechanical Compliance

MIL-STD-810: Environmental Durability

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

