

Page



Powertec Wireless Technology  
ABN: 42 082 948 463  
PO Box 1034, Ashmore City  
Queensland, Australia, 4214  
sales@powertec.com.au  
1300 769 378

# **Poynting XPOL-24, 4x4 MIMO 4G-5G antenna, 617 to 4200 MHz, N Female**

SKU  
ANT-PY-00053  
MPN  
A-XPOL-0024-V1-02

## Description

The Poynting XPOL-24 is a versatile 4x4 MIMO antenna designed for seamless 4G and 5G connectivity, covering a broad frequency range from 617 to 4200 MHz. This antenna is ideal for high-speed wireless data applications, including residential 4G LTE, GSM, M2M, and DTV, making it suitable for consumer, broadcast, and telecommunications markets.

Constructed with durable ASA plastic, the XPOL-24 withstands harsh outdoor conditions with an IP65 ingress protection rating and operates effectively in temperatures from -40°C to 80°C. Weighing 3.17 kg and featuring dimensions of 290 x 444 x 110 mm, its robust design ensures reliable performance in diverse environments.

Equipped with four N Female RF connectors, the XPOL-24 supports a 50  $\Omega$  impedance and up to 10 W input power, ensuring optimal signal transmission. It offers impressive gain values, reaching up to 11.0 dBi, and maintains a VSWR of <2.0:1 across its frequency ranges, ensuring efficient signal reception and transmission.

Poynting, a leading global innovator in antenna solutions, designs and manufactures its products to meet stringent CE and RoHS compliance standards. Headquartered in Johannesburg, with operations in China and a European office in Munich, Poynting delivers cutting-edge connectivity solutions worldwide.



## [Poynting](#)

Poynting is a top global provider of integrated antenna solutions, responsible for the innovation, design and manufacture of its market-leading products. Established as a consultancy in 1990, Poynting evolved into an official PTY in

1997 and in 2001 established Poynting Antennas. It caters antenna solutions for primarily wireless high speed data applications, including residential 4G LTE as well ...

## RF Specification

Start Frequency

617 MHz

Stop Frequency

4200 MHz

Max. Input Power

10 W

Polarisation

[Vertical \(V\)](#)

Input Impedance

50  $\Omega$

RF Connectors

### Ports RF Interface Body Shape

1      [N Female](#)      [Straight](#)

Frequency Test Data

### Start Freq. Stop Freq. Peak Gain VSWR

617 MHz	960 MHz	8.5 dBi	< 2:1
---------	---------	---------	-------

1710 MHz	2700 MHz	8.5 dBi	< 2:1
----------	----------	---------	-------

3400 MHz	4200 MHz	11 dBi	< 2:1
----------	----------	--------	-------

## Physical Specification

Input Ports

4

MIMO

[4x4 MIMO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

80 °C

Dimensions

290 x 444 x 110

Ingress Protection

[IP65](#)

Materials

[ASA Plastic](#)

Weight

3.17 kg

Compliance/Certifications

CE

,

RoHS

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

