

# Poynting WLAN-60, Dual Band WiFi antenna, 2400 to 6000 MHz

SKU: ANT-PY-00062

MPN: A-WLAN-0060-V1

## Description

The Poynting WLAN-60 is a dual-band WiFi antenna designed for versatile applications across consumer, broadcast, and telecommunications markets. Operating within a frequency range of 2400 to 6000 MHz, this panel/sector antenna is ideal for high-speed data needs, including 4G LTE, GSM, M2M, and digital TV applications. Made from durable ABS plastic, it features an IP65-rated enclosure, ensuring robust performance in harsh environments from -40°C to 70°C.

The antenna delivers exceptional RF performance with a peak gain of up to 18.0 dBi, supported by a 50 Ω impedance and up to 10 W of input power. Its linear polarisation and 1x SMA female connector facilitate straightforward integration into various systems. The WLAN-60 meets CE, RoHS, and ISO 9001 quality standards, and its durability is validated by MIL-STD-810 compliance.

Poynting, a leader in integrated antenna solutions, designs and manufactures this innovative product with a focus on...

[Read More](#)

## RF Specification

Start Frequency:	2400 MHz	Polarisation:	Linear
Stop Frequency:	6000 MHz	Input Impedance:	50 Ω
Max. Input Power:	10 W	Poynting is the global provider of integrated antenna solutions, responsible for the innovation, design and manufacture of its market-leading products. Established as a consultancy in 1990, Poynting evolved into an official PTY in 1997 and in 2001 established Poynting Antennas. It caters antenna solutions for primarily wireless high speed data applications, including residential 4G LTE as well ...	

RF Connectors

**Ports**

1

**RF Interface**

SMA Female

**Body Shape**

Straight

## Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR
2400 MHz	2500 MHz	13 dBi	< 2.5:1
3300 MHz	3800 MHz	15 dBi	< 2.5:1
5000 MHz	6000 MHz	18 dBi	< 2.5:1

# Physical Specification

Subtype:	Panel / Sector	Dimensions:	240 x 240 x 60
Input Ports:	1	Ingress Protection:	IP65
MIMO:	1x1 SISO	Materials:	ABS Plastic
Min. Operating Temperature:	-40 °C	Weight:	0.76 kg
Max. Operating Temperature:	70 °C	Compliance/Certifications:	CE
		RoHS	'
		ISO 9001 Quality Management	
		Mechanical Compliance:	MIL-STD-810: Environmental Durability

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

