

Poynting WLAN-61, 4x4 MIMO Dual Band WiFi antenna; 2400 to 6000 MHz

SKU: ANT-PY-00063

MPN: A-WLAN-0061-V1

Description

The Poynting WLAN-61 is a high-performance 4x4 MIMO Dual Band WiFi antenna, designed for optimal connectivity across a wide frequency range of 2400 to 6000 MHz. With a robust ABS plastic construction and an IP65 ingress protection rating, this antenna is built to withstand harsh environmental conditions, operating effectively in temperatures from -40°C to 70°C.

The antenna supports advanced wireless applications by offering four RF connections through SMA Female interfaces, ensuring efficient data transmission. Its dual slant $\pm 45^\circ$ polarisation enhances signal reliability and performance, making it an ideal solution for demanding applications such as 4G LTE, GSM, M2M, and DTV. The WLAN-61's peak gains of 9.0 dBi at 2400-2500 MHz and 11.0 dBi at 5000-6000 MHz provide superior signal strength, while maintaining a VSWR of less than 2.0:1 for optimal impedance matching.

Certified to CE, ISO 9001, and RoHS standards, and tested to meet MIL-STD...

[Read More](#)



Poynting

Poynting is a top global provider of integrated antenna solutions, responsible for the innovation, design and manufacture of its market-leading products. Established as a consultancy in 1990, Poynting evolved into an official PTY in 1997 and in 2001 established Poynting Antennas. It caters antenna solutions for primarily wireless high speed data applications, including residential 4G LTE as well ...

RF Specification

Start Frequency:	2400 MHz	Polarisation:	Dual Slant ±45°
Stop Frequency:	6000 MHz	Input Impedance:	50
Max. Input Power:	10 W		

RF Connectors

Ports	RF Interface	Body Shape
1	SMA Female	Straight

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR
2400 MHz	2500 MHz	9 dBi	< 2:1
5000 MHz	6000 MHz	11 dBi	< 2:1

Physical Specification

Input Ports:	4	Dimensions:	240 x 240 x 60
MIMO:	4x4 MIMO	Ingress Protection:	IP65
Min. Operating Temperature:	-40 °C	Materials:	ABS Plastic
Max. Operating Temperature:	70 °C	Weight:	0.76 kg
Compliance/Certifications:			CE
ISO 9001 Quality Management			,
RoHS			,
Mechanical Compliance:		MIL-STD-810: Environmental Durability	

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

