

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Poynting GPS-1, Low Profile Active GPS Antenna, 1575.42 to 1600 MHz

SKU
ANT-PY-00069
MPN
A-GPS-0001-V2-01

Description

The Poynting GPS-1 is a low-profile, active GPS antenna operating within the 1575.42 to 1600 MHz range, designed for robust GNSS applications. With a compact size of 99.3 x 36 mm and a weight of 0.31 kg, it is constructed from durable polycarbonate and boasts an IP68 ingress protection rating, ensuring reliability in harsh environments with temperatures ranging from -40 °C to 80 °C.

This antenna, featuring a single RF connection via an SMA Male interface, is ideal for precise GPS applications due to its right-hand circular polarisation and impressive 21 dBic gain. The integrated Low Noise Amplifier (LNA) enhances signal clarity with a noise figure of ≤ 1.5 dB and operates efficiently within a voltage range of 2.7 V to 3.3 V.

Compliant with CE, RoHS, and ISO 9001 standards, the GPS-1 is suitable for high-precision applications in telecommunication, broadcast, and consumer markets. Poynting, a renowned brand originating from South Africa...

[Read More](#)



[Poynting](#)

Poynting is a top global provider of integrated antenna solutions, responsible for the innovation, design and manufacture of its market-leading products.

Established as a consultancy in 1990, Poynting evolved into an official PTY in 1997 and in 2001 established Poynting Antennas. It caters antenna solutions for primarily wireless high speed data applications, including residential 4G LTE as well ...

RF Specification

GPS

Gain (Zenith)

21 dBic

Start Frequency

1575.42 MHz

Stop Frequency

1600 MHz

Input Impedance

50 Ω

Polarisation

[Right Hand Circular \(RHCP\)](#)

Low Noise Amplifier (LNA)

LNA Gain

21 dBic

Noise Figure

≤ 1.5 dB

Min. Operating Voltage

2.7 V

Max. Operating Voltage

3.3 V

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
-------	--------------	------------	--------------	--------

1	SMA Male	Straight	A-302	2000 mm
---	--------------------------	--------------------------	-----------------------	---------

Physical Specification

Input Ports

1

MIMO

[1x1 SISO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

80 °C

Dimensions

99.3 x 36

Ingress Protection

[IP68](#)

Materials

[Polycarbonate \(PC\)](#)

Weight

0.31 kg

Compliance/Certifications

CE

,

RoHS

,

ISO 9001 Quality Management

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

