

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Poynting OMNI-155, Omni- Directional, Rhyno, 4G antenna, 703 to 803 MHz

SKU
ANT-PY-00079
MPN
A-OMNI-0155-V1-01

Description

The Poynting OMNI-155 is a robust, omni-directional 4G antenna specifically designed for versatile applications in wireless data communication. Operating within the 703 to 803 MHz frequency range, it is ideal for residential 4G LTE, GSM, M2M, and DTV applications. Its monopole design ensures a 360° azimuth beamwidth, delivering consistent performance with a peak gain of 1.5 dBi.

Engineered from durable ASA plastic, the OMNI-155 boasts an IP68 ingress protection rating, making it suitable for harsh environmental conditions, withstanding temperatures from -40 °C to 80 °C. Its compliance with CE and RoHS standards, along with MIL-STD-810 environmental durability, ensures reliability and safety.

The antenna features a single SMA Male connector with a 1000 mm RG-58 cable, providing seamless integration into various systems. With a 50 Ω impedance and a power handling capability of up to 10 W, the OMNI-155 facilitates robust and efficient signal...

[Read More](#)



[Poynting](#)

Poynting is a top global provider of integrated antenna solutions, responsible for the innovation, design and manufacture of its market-leading products.

Established as a consultancy in 1990, Poynting evolved into an official PTY in 1997 and in 2001 established Poynting Antennas. It caters antenna solutions for primarily wireless high speed data applications, including residential 4G LTE as well ...

RF Specification

LTE

Start Frequency

703 MHz

Stop Frequency

803 MHz

Max. Input Power

10 W

Polarisation

[Vertical \(V\)](#)

Input Impedance

50 Ω

RF Connectors

Ports RF Interface Body Shape Cable Series Length

1 [SMA Male](#) [Straight](#) [RG-58](#) 1000 mm

Frequency Test Data

Start Freq. Stop Freq. Peak Gain VSWR Azimuth

703 MHz 803 MHz 1.5 dBi < 2:1 360°

Physical Specification

Subtype

[Monopole](#)

Input Ports

1

MIMO

[1x1 SISO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

80 °C

Dimensions

155 x 70

Ingress Protection

[IP68](#)

Materials

ASA Plastic

Weight

0.35 kg

Compliance/Certifications

CE

,

RoHS

Mechanical Compliance

MIL-STD-810: Environmental Durability

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

