



CradlePoint 170801-000 Cellular Antenna, Charcoal, 600 MHz - 6 GHz, SMA for IBR1700/IBR900, AER2200, E300/E3000, MC400

SKU: M2M-CP-00105 MPN: 170801-000

Description

The CradlePoint 170801-000 Cellular Antenna is a versatile and robust solution designed for a range of Cradlepoint devices, including the IBR1700, IBR900, AER2200, E300, E3000, and MC400. Operating across a wide frequency range from 600 MHz to 6 GHz, this hinged antenna is ideal for enhancing LTE and 5G connectivity in various applications, such as connecting remote sites, vehicles, mobile workforces, and IoT devices.

The antenna features a single SMA Male interface with a hinging connector, facilitating straightforward installation and integration with existing setups.

As part of Cradlepoint's innovative wireless solutions, this antenna helps unlock the potential of wireless WAN edge technology, enabling seamless and secure connectivity beyond the limitations of wired networks.



Cradlepoint



Cradlepoint is a Boise, Idaho, company with a mission of enabling customers to Connect Beyond the limits of wired networks. We unlock the transformative power of today's LTE and 5G cellular networks to provide an agile, reliable, and pervasive Wireless WAN edge.

Through Cradlepoint's solutions, companies can connect sites, vehicles, mobile workforces, and IoT devices in a simple and secure way ...

RF Specification

Start Frequency:	615 MHz	Polarisation:	Linear
Stop Frequency:	6000 MHz	Input Impedance:	50

RF Connectors

PortsRF InterfaceBody Shape1SMA MaleStraight

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR
615 MHz	960 MHz	1.1 dBi	< 3.6:1
1445 MHz	1515 MHz	0.6 dBi	< 2.6:1
1520 MHz	1640 MHz	0.37 dBi	< 2.5:1
1710 MHz	2700 MHz	2.63 dBi	< 2.5:1
3000 MHz	3700 MHz	4 dBi	< 2.5:1
3700 MHz	5000 MHz	4 dBi	< 4.5:1
5150 MHz	5925 MHz	4.39 dBi	< 4.5:1

Physical Specification

Subtype: Hinged Terminal Dimensions: 180 Input Ports: 1 Ingress Protection: IP67 MIMO: 1x1 SISO Materials: Plastic Min. Operating Temperature: -40 °C Weight: 0.15 kg Max. Operating Temperature: 85 °C Compliance/Certifications: RoHS				
MIMO: 1x1 SISO Materials: Plastic Min. Operating Temperature: -40 °C Weight: 0.15 kg Max. Operating Temperature: 85 °C Compliance/Certifications: RoHS	Subtype:	Hinged Terminal	Dimensions:	180
Min. Operating Temperature: -40 °C Weight: 0.15 kg Max. Operating Temperature: 85 °C Compliance/Certifications: RoHS	Input Ports:	1	Ingress Protection:	IP67
Max. Operating Temperature: 85 °C Compliance/Certifications: RoHS	MIMO:	1x1 SISO	Materials:	Plastic
	Min. Operating Temperature:	-40 °C	Weight:	0.15 kg
Mechanical Compliance: IFC 60068-2-6: Vibration	Max. Operating Temperature:	85 °C	Compliance/Certifications:	RoHS
Mechanical compilation			Mechanical Compliance:	IEC 60068-2-6: Vibration

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

