

Peplink Mobility 40G (Puma 401), 4 x LTE/5G, 1 x GPS, IP67, QMA, Black, 0.3M

SKU: PUMA-401-Q-B-1
 MPN: ANT-MB-40G-Q-B-1

Description

The Peplink Mobility 40G (Puma 401) is a robust and versatile antenna designed to enhance mobile connectivity and GPS functionality across various demanding environments. Equipped with 4x4 MIMO LTE/5G capabilities, it ensures reliable and high-speed data transmission, making it ideal for applications in transportation, maritime, and remote installations where consistent connectivity is crucial. Its frequency range from 617 MHz to 6000 MHz covers a broad spectrum, supporting both current and emerging cellular technologies.


The antenna's rugged construction, featuring IP68 ingress protection, guarantees durability against harsh weather conditions, while its ABS plastic and polycarbonate materials provide a UV-stable housing. This makes it suitable for prolonged outdoor deployment, ensuring longevity and performance stability. The integrated GPS functionality, with a gain of 1.6 dBic and right-hand circular polarisation, enhances location...

[Read More](#)



RF Specification

Cellular

	Peplink 617 MHz Peplink makes connectivity reliable. Peplink's ecosystem, SpeedFusion technology and SD-WAN routers have been deployed around the world, helping thousands of customers from many industries increase bandwidth, enhance Internet reliability, reduce connectivity cost, or enable new deployment possibilities.	Polarisation: Linear
	6000 MHz Founded by Alex Chan in Hong Kong in 2006, today Peplink is based in Mountain View, California.	Input Impedance: 50
Start Frequency: Stop Frequency: Max. Input Power:	10 W	

RF Connectors

Ports	RF Interface	Body Shape	Length
1	QMA Male	Straight	300 mm

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain
617 MHz	960 MHz	0.3 dBi
1710 MHz	2700 MHz	5.1 dBi
3400 MHz	4200 MHz	5.8 dBi
4900 MHz	6000 MHz	7 dBi

GPS

Gain (Zenith):	1.6 dBic	Input Impedance:	50
Start Frequency:	1561 MHz	Polarisation:	Right Hand Circular (RHCP)
Stop Frequency:	1602 MHz		

Low Noise Amplifier (LNA)

LNA Gain:	28 dBic	Min. Operating Voltage:	3.3 V
Noise Figure:	≤ 1.5 dB	Max. Operating Voltage:	3.3 V
Power Consumption:	< 8.5 mW		

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	QMA Male	Straight	RG-174	300 mm

Physical Specification

Subtype:	Panel / Sector	Dimensions:	36 x 130
Input Ports:	2	Ingress Protection:	IP68
MIMO:	4x4 MIMO	Materials:	ABS Plastic, Polycarbonate (PC)
Min. Operating Temperature:	-40 °C	Compliance/Certifications:	RoHS
Max. Operating Temperature:	80 °C	Mechanical Compliance:	IEC 60529: IP Code
		MIL-STD-810: Environmental Durability	

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

