

Page



Powertec Wireless Technology  
ABN: 42 082 948 463  
PO Box 1034, Ashmore City  
Queensland, Australia, 4214  
sales@powertec.com.au  
1300 769 378

# **Blackhawk 4G Omni High Gain Antenna, 698 to 2700 MHz, N Female**

SKU  
ANT-BH-OM-204  
MPN  
VCOL-6927-6.N2  
Barcode  
9337692000447

## Description

Blackhawk wideband omnidirectional antennas provide high gain across the full cellular band 700 to 2700 MHz regardless of mounting direction, allowing quick and easy installation with no technical know-how required. The antenna provides exceptional omnidirectional performance on almost all mobile networks globally.

The antenna provides a 6 dBi gain across the 4G-5G low and mid-bands, the ideal gain figure for areas with weak mobile signal.

The true wideband performance has been achieved through a clever engineering design utilising multi-sized collinear radiators and microwave-grade combiners, demonstrating consistently high gain with exceptional azimuthal stability.

The Blackhawk Wideband Omni Antenna provides an ideal solution for 4G-5G voice and data applications. With the implementation of new 4G and 5G frequencies across a broad range of radio spectrum, the use of a wideband antenna is necessary to see the full functionality of LTE-Advanced and 5G networks.

This antenna is ideal for use in rural and regional areas with marginal mobile network coverage.

[Read More](#)



## [Powertec](#)

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

# RF Specification

Start Frequency

700 MHz

Stop Frequency

2700 MHz

Max. Input Power

100 W

Polarisation

[Vertical \(V\)](#)

Input Impedance

50  $\Omega$

RF Connectors

## Ports RF Interface Body Shape

1      [N Female](#)      [Straight](#)

Frequency Test Data

### Start Freq. Stop Freq. Peak Gain VSWR Azimuth Elevation

698 MHz	890 MHz	5 dBi	< 1.6:1	360°	38°
890 MHz	960 MHz	4.5 dBi	< 1.9:1	360°	40°
1695 MHz	2200 MHz	6 dBi	< 2:1	360°	20°
2200 MHz	2700 MHz	6.5 dBi	< 2.3:1	360°	15°

Polar Patterns


Start Frequency

698 MHz


Stop Frequency

960 MHz

### Azimuth Polar Plot



### Elevation Polar Plot




Start Frequency

1695 MHz


Stop Frequency

2700 MHz

### Azimuth Polar Plot



### Elevation Polar Plot



# Physical Specification

Subtype

[Collinear](#)

Input Ports

1

MIMO

[1x1 SISO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

65 °C

Dimensions

680 x 63 x 63

Materials

[Polyvinyl Chloride \(PVC\)](#)

Mounting

[Pole Clamp 30 to 52 mm ø](#)

Weight

1.9 kg

Compliance/Certifications

ISO 9001 Quality Management

,

RoHS

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

