

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Cambium Networks C050045B002B 5 GHz PTP 450i END, Integrated High Gain Antenna (ROW)

SKU
WIF-CB-00075
MPN
C050045B002B

Description

Cambium's PTP 450i is a ruggedised all-integrated 5 GHz point-to-point microwave radio capable of providing data connectivity up to 300 Mb/s with very high reliability.

PTP 450i provides industrial grade performance with IP66 / IP67 ingress protection, while maintaining a very reasonable price point. The unit can be set to use any 40 MHz channel within the entire 5 GHz band to achieve in excess of 300 Mbps of real throughput using modulation up to 256QAM and 2x2 MIMO.

With its Motorola legacy and industrial metal enclosure it should be no surprise the unit boasts a working life (MTBF) of over 40 years.

The C050045B002A variation of the PTP 450i integrates a medium-high gain 23 dBi patch array antenna, with no exposed connections for the highest possible reliability.

[Read More](#)





Cambium Networks

Cambium Networks enables service providers; enterprises; governmental and military agencies; oil, gas and utility companies; Internet service providers; and public safety organizations to build powerful communications networks, reach users from 200 kilometers across mountain tops down to their devices, and intelligently manage their business Wi-Fi infrastructure through end-to-end network ...

Network Interfaces

Wireless Interfaces

Topology

[Point-to-Point \(P2P\)](#)

Max. Throughput

300 Mb/s

Encryption

[AES-128](#)

Max. Clients

1

Latency

5 ms

Aggregate Channel Width

40 MHz

Transmit Power

28 dBm

Wireless Bands	Start Frequency	Stop Frequency	MIMO	Channel Width	Modulation	Max. Data Rate
-------------------	--------------------	-------------------	------	------------------	------------	----------------------

5 GHz4900 MHz5925 MHz2x2 MIMO40 MHz256QAM300 Mb/s

Ethernet Interfaces

Interface	Quantity	Function	Signalling	PoE Input
RJ45 Copper	1	Data + PoE In	100BASE-T, 1000BASE-T	802.3at PoE+
RJ45 Copper	1	Aux + PoE Out	100BASE-T, 1000BASE-T	802.3at PoE+

Antenna Specifications

Start Frequency

4900 MHz

Stop Frequency

5925 MHz

Polarisation

Dual Pol (V, H)

Input Impedance

50 Ω

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	Return Loss	VSWR	Azimuth	Elevation
4900 MHz	5925 MHz	23 dBi	> 14 dB	< 1.5:1	10°	10°

Polar Patterns


Start Frequency

5150 MHz


Stop Frequency

5850 MHz

Azimuth Polar Plot



Elevation Polar Plot



Physical Specification

Subtype

[Wireless Bridge](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

75 °C

Ingress Protection

[IP67](#)

MTBF

> 350000 h

Dimensions

64 × 310 × 310 mm

Weight

2.5 kg

Materials

[Aluminium](#)

Mounting

Cambium 4/8-Bolt Pattern

Compliance/Certifications

[CE](#)

,

[RCM](#)

Power Specifications

Max. Consumption

30 W

Typical Consumption

15 W

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

