

GC76 Series Galvanised Steel Headframe, 2-Sector

SKU: MAS-BH-00327

MPN: AP-GC76-HF2

Description

APAC's Socket Mounted Two-Sector Headframe is a durable galvanised steel mast head that is attached by its central tube slipping over the GC76 mast spigot and securing in place using M10 set screws.

Each 900 mm vertical mount is constructed from 48 mm diameter CHS steel and secured to a centre column via a 48 mm diameter tube to provide a high degree of rigidity and minimal deflection/torquing.

The two vertical mounts are separated approximately 800 mm (pipe centre to centre), with a total width of 848 mm.



Physical Specification

Subtype:	Headframe	Mounting:	Pole Socket for 76 mm OD Spigot
Dimensions:	848 x 89 x 900 mm		

Available Interfaces

Quantity	Mounting	Details
2	Pole 48 mm	900 mm lengths

Subcomponents

Quantity	Name	Materials	Material Finish
1	Welded Frame, 48.3 O/D x 2.90 mm CHS Pipe	Steel Hollow Section AS 1163-C350LO	Hot-Dip Galvanised
1	Welded Socket 88.9 O/D x 3.25 mm CHS Pipe	Steel Hollow Section AS 1163-C350LO	Hot-Dip Galvanised
1	M10 Bolts used as Set Screws	Steel	Hot-Dip Galvanised

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

