

# Electric Winch-Up Mast 1.8m Retracted, 7.8m Extended, 50kg Payload, Electric Rotator, 1x Cat6 1x PTL-240 Spiral Cable

SKU: MAS-BH-00344


MPN: AP-TM-CWU8E-6S-2C

## Description


This is a traditional cable-driven winch-up mast that comprises of 5x 1.5 metre hot-dip galvanised sections that telescope outward from a powdercoated steel base section. The extended height is 7.8 metres, which packs down to 1.8 metres. The mast has been engineered for a 50 kg payload in up to 120 km/h winds.

The mast has two spiral cables which each contain 1x PTL-240 Ultra-Flex Coaxial Cable, 1x Cat-6 Ethernet Cable, and DC power cables. The primary spiral cable runs to the top of the mast, and the secondary spiral cable runs to the mast mid-point. The DC powered Mast Rotator, which allows equipment to be panned a full 360° can be placed either at the top of the mast or at the mid-point using an optional bracket.

The mast is lowered and raised by a 1100 kg 12/24 Vdc Electric Winch, which is operated by a hand controller.



## Physical Specification

Subtype:	Retractable Mast	Dimensions:	550 x 500 x 1,820 mm
Weight:	74.5 kg	Nominal Height:	8 m
Installation:	 <p>APAC Infrastructure is an Australian metal fabrication company dedicated to high tech industries in the commercial, industrial, and defence sectors. Our team is committed to evolving our solutions to meet the rapidly changing needs of our rapidly changing world, ensuring your team deliver solutions at the very forefront of technological development. APAC develops made-to-measure height systems for ...</p>	Wind Survival:	33 m/s

Retracted Height:	1.8 m	Extended Height:	7.8 m
Max. Payload:	50 kg	Lifting Time:	< 2 min
No. Sections:	6	Locking:	Non-Locking
Lifting Mechanism:	Winch		

#### Subcomponents

Quantity	Name	Materials	Material Finish
1	1.5 m Top Section, 60x60 mm	Steel	Hot-Dip Galvanised
1	1.5 m Second Section, 80x80 mm	Steel	Hot-Dip Galvanised
1	1.5 m Third Section, 100x100 mm	Steel	Hot-Dip Galvanised
1	1.5 m Fourth Section, 120x120 mm	Steel	Hot-Dip Galvanised
1	1.5 m Fifth Section, 140x140 mm	Steel	Hot-Dip Galvanised
1	1.5 m Base Section, 160x160 mm	Steel	Powdercoated
1	Full-Length Cable Spiral, 1x PTL-240, 1x Cat-6 Ethernet, 1x DC Power Cable 6mm2		
1	Half-Length Cable Spiral, 1x PTL-240, 1x Cat-6 Ethernet, 1x DC Power Cable 6mm2		

Quantity	Subcomponent
1	Runva EWP2500U Electric Winch
1	Mast Rotator for APAC Winch-Up Masts

#### Available Interfaces

Quantity	Mounting	Details
1	Retractable Mast Bolt Pattern	Attachment of mast-specific headframes and devices
1	Rotator Bolt Pattern	Attachment of rotator-specific headframes and devices
1	Retractable Mast Mid-Section	Attachment of purpose-built bracketry for mast mid-point

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

