

# APAC AMT Alloy Modular Trailer, Single-Axle, Base Chassis

SKU: MAS-BH-00373  
 MPN: AP-AMT-SA

## Description


APAC's Single-Axle Alloy Modular Trailer is part of the company's AMT Platform, a mounting system built from interchangeable modules that allows simple reconfiguration and redeployment.

This is a Trailer Base Chassis, which can be thought of as the base building block from which other modules and subsystems are attached. It is a Single-Axle Trailer, which provides a deck length of 2.6 m and width of 1.6 metres. This model is shorter than the dual-axle trailer by 400 mm.

The Chassis is manufactured in Queensland using heavy gauge medium-structural grade aluminium.



## Physical Specification

Subtype:	Trailer	Dimensions:	4,500 × 2,500 × 990 mm
Weight:	419 kg		
No. Axles:	1	Deck Height:	850 mm
Trailer Connector:	 <b>APAC Infrastructure</b> 50 mm Ball Hitch	Trailer Connector:	7-Pin Flat
Braking System:	Mechanical Brakes	Suspension:	Leaf Spring
Running Clearance:	600 mm		

APAC Infrastructure is an Australian metal fabrication company dedicated to high tech industries in the commercial, industrial, and defence sectors. Our team is committed to evolving our solutions to meet the rapidly changing needs of our rapidly changing world, ensuring your team deliver solutions at the very forefront of technological development. APAC develops made-to-measure height systems for ...

Available Interfaces

Quantity	Mounting
7	APAC AMT Cross Member
1	APAC AMT Flooring Attachment

Subcomponents

Quantity	Name
4	Levelling Jack, 1500 kg Rated
1	Mechanical Drum Axle 6-Stud, 1400 kg Rated
3	16 x 8 x 245 Landcruiser 0 Offset Rims
3	245/75 R16 Light Truck Tyres, incl. 1x Spare Tyre
1	Heavy Duty Safety Chain Kit, 10 mm Chain, 2500 kg Rated
1	10" Solid Rubber Swivel Jockey Wheel, Heavy Duty Brackets
2	Eye-to-Eye Leaf Spring Suspension, 1500 kg rated
1	50 mm Ball Plunger Coupling, 3500 kg Rated

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

