

Victron Solar Panel 175W-12V Mono 1485x668x30mm series 4a

SKU: ENG-VT-00063

MPN: VIC.SPM041751200

Description

- Low voltage-temperature coefficient enhances high-temperature operation.
- Exceptional low-light performance and high sensitivity to light across the entire solar spectrum.
- 25 Year limited warranty on power output and performance.
- 5 Year Limited warranty on materials and workmanship.
- Sealed, waterproof, multi-functional junction box gives high level of safety.
- High performance bypass diodes minimise the power drop caused by shade.
- Advanced EVA (Ethylene Vinyl Acetate) encapsulation system with triple-layer back sheet meets the most stringent safety requirements for high-voltage operation.
- A sturdy, anodised aluminium frame allows modules to be easily roof-mounted with a variety of standard mounting systems.
- Highest quality, high-transmission tempered glass provides enhanced stiffness and impact resistance.
- Pre wired quick-connect system with MC4 (PV-ST01) connectors.



Victron Energy

Victron Energy is a Dutch company specialized in the design and manufacture of products for battery-based energy systems. Since 1975, Victron Energy has grown from a one-office technology startup to become an international enterprise with nearly 1,000 different products sold worldwide. In the off-grid sector, we offer reliable and innovative solutions from solar home systems to mini-grids. Our ...

Electrical Specification (STC)

Nominal Power Pmax:	175 W	Max-Power Voltage Vmp:	19.4 V
Max-Power Current Impp:	9.03 A	Open-Circuit Voltage Voc:	23.7 V
Short-Circuit Current Isc:	9.89 A	Cells in Series:	72
Max System Voltage:	1000 V	Power Tolerance:	5.25 W
Temp. Coefficient Pmax:	-0.45 %/°C	Temp. Coefficient Voc:	-0.35 %/°C
Temp. Coefficient Isc:	0.04 %/°C		

Physical Specification

Dimensions:	1,485 × 668 × 30 mm	Weight:	11 kg
Cell Type:	Monocrystalline	Min. Operating Temperature:	-40 °C
Mounting:	Solar Rail Clamp	Max. Operating Temperature:	85 °C

Power Connections

Quantity	Power Connector	Cable Series	Length
1	MC4 Female	4mm ² Single Core DC Power Cable	900 mm
1	MC4 Male	4mm ² Single Core DC Power Cable	900 mm

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

