

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Teltonika RUTX12 - 3G/4G CAT6 Dual Module Router with WiFi / GPS / Bluetooth

SKU
M2M-TE-00017
MPN
RUTX12
Barcode
4779027312743

Description

RUTX12 is the first router in its class to offer twin 4G modem modules, allowing concurrent connectivity of two mobile networks. This dual connectivity mode provides 2+0 style failover protection and load balancing features. RUTX12 is an LTE-Advanced modem providing Cat 6 data rates up to 600 Mb/s via 2C CA in load-balancing mode between the two LTE chipsets.

The router's two modem chips each have two antenna connectors, providing four 4G antenna connections. This allows aiming of two separate 2x2 MIMO external antennas to two different towers.

RUTX12 provides high speed local WiFi connectivity, operating as a Wave-2 802.11ac Dual Band WiFi access point with speeds up to 867 Mb/s. The modem also supports USB along with Bluetooth LE for simplified industrial IO with its own dedicated antenna connection.

The modem has a built in GNSS / GPS module, allowing customised tracking to be installed on the modem, along with remote management through ...

[Read More](#)

This device is developed from a beefed up Quad Core ARM Cortex A7 717 MHz CPU and 256 MB DDR3 RAM SBC and uses two integrated Quectel EP06-E Category 6 LTE-Advanced modules.

RUTX12 uses a fully open source and customisable OpenWRT Linux OS with a Busybox shell. Using only a portion of its 256 MB flash memory allows additional daemons and custom services to be run to meet your specific application.

[Read More](#)



Teltonika

In 21 years we have launched to mass production over 100 different devices in IoT, Networking, Connected vehicles, Asset and personal Tracking areas. That makes over 8.600.000 million devices sold worldwide in over 150 different countries. Although these numbers are impressive, Teltonika is more than that – we are about innovating, inspiring, connecting, educating and reliable partnership.

By ...

Network Interfaces

Wireless Interfaces

Cellular Module

Technologies

[3G UMTS](#), [4G LTE](#)

Failover

Automatic

Chipset/Module

Quectel EP06

4G LTE Specifications

MIMO

[2x2 MIMO](#)

LTE Bands

[B1](#)

,

[B3](#)

,

[B5](#)

,

[B7](#)

,

[B8](#)

,

[B20](#)

,

[B32](#)

,

[B38](#)

,

[B40](#)

,

[B41](#)

DL Category

Cat 6

UL Category

Cat 5

Carrier Aggregation

2C CA

SIM Cards

Quantity	SIM Type
2	Standard SIM (2FF)

Modem RF Connectors

RF Connector	Function	Quantity	RF Interface
--------------	----------	----------	--------------

Cellular		2	SMA Female
----------	--	---	----------------------------

Bluetooth Interface

Protocol

[Bluetooth 4.0](#)

Device RF Interface

RF Connector	Function	Quantity	RF Interface
--------------	----------	----------	--------------

Bluetooth		1	RP-SMA Female
-----------	--	---	-------------------------------

GNSS Module

Technologies

[BeiDou](#), [Galileo](#), [GLONASS](#), [GPS](#), [QZSS](#)

Device RF Interface

RF Connector	Function	Quantity	RF Interface
--------------	----------	----------	--------------

GNSS		1	SMA Female
------	--	---	----------------------------

WiFi Module

No. Radios

2

Max. Throughput

867 Mb/s

Max. Clients

100

No. Antennas

2

WiFi Radios

Radio Name (Optional)	WiFi Standard	Frequency Bands	MIMO
Radio 2.4 GHz	802.11n	2.4 GHz	2x2 MIMO
Radio 5 GHz	802.11ac Wave 2	5 GHz	2x2 MIMO

WiFi RF Connectors

RF Connector	Function	Quantity	RF Interface	Notes
WiFi		2	RP-SMA Female	Both 2.4 and 5 GHz Radios

Ethernet Interfaces

Interface	Quantity	Function	Signalling
RJ45 Copper	4	LAN	100BASE-T , 1000BASE-T

Interface	Quantity	Function	Signalling
RJ45 Copper	1	WAN	100BASE-T , 1000BASE-T

Physical Specification

Subtype

[Cellular Modem](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

75 °C

Dimensions

132 × 95 × 44 mm

Weight

540 g

Materials

[Aluminium](#)

Mounting

Teltonika Modem Screw Pattern

Compliance/Certifications

[RCM](#)

IO Interfaces

IO Connector Quantity

USB-A 2.0 1

Power Specifications

Max. Consumption

22 W

Typical Consumption

4 W

Power Interface

Power Connector	Min. Input Voltage	Max. Input Voltage	Voltage Type
Terminal Block, 4-Position	9 V	50 V	DC

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility

therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

