Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Starlink Standard Actuated Dish, Gen 2 (REV3)

MPN
UTA-212

Description

Starlink's Generation 2 User Terminal, known as the Standard Actuated Dish, or "Rectangular Dishy" is a satellite terminal provided by Starlink as the main user

equipment between November 2021 and late 2023. The unit is referred to as the Generation 2 (Rev3) UT. Generation 1 (Rev1 & Rev2) refer to the "Round Dishy". Depending on when the UT was manufactured it may have a sub-version of rev3_proto0, rev3_proto1, or rev3_proto2.

The antenna unit UTA-212 connects to its corresponding router UTR-211. Specification here refers to the UTA-212 only.

In general, the Starlink Gen2 User Terminal is a satellite transceiver which uses digital beamformers and an Electronic Steerable Antenna to track and maintain connectivity with LEO satellites as they move overhead. Gen2 uses motors to adjust azimuth and elevation to position the phased array orthogonally (ideally 90°) to the direction of the satellite and therefore maximising the effective antenna ...

Read More

Information on Starlink UTs is difficult to piece together. If you notice an error please reach out to our team.





Starlink

Starlink, initiated by US company SpaceX in January 2015, is a satellite network project aimed at providing satellite internet connectivity. The project's primary objective is to deliver broadband services globally, particularly to underserviced areas of the planet. Starlink's constellation comprises thousands of mass-produced small satellites, orbiting in low Earth orbit (LEO), working in ...

Network Interfaces
Wireless Interfaces
Topology
Multipoint Terminal/Subscriber
Max. Throughput
720 Mb/s
Encryption
AES-256
Max. Clients
1
Latency
30 ms
Aggregate Channel Width
240 MHz

Starlink Transceiver

Transmit Power
34.4 dBm
Receive Sensitivity
-89 dBm

Wireless Bands	Path Mode	Start Frequency	Stop Frequency	MIMO	Channel Width	Modulation	Max. Data Rate
X Band	Receive	10700 MHz	12700 MHz	1x1 SISO	240 MHz	64QAM	720 Mb/s
Ku Band	Transmit	14000 MHz	14500 MHz	1x1 SISO	60 MHz	64QAM	180 Mb/s

Ethernet Interfaces

Interface	Quantity	Function	Signalling	PoE Input
SPX 20-Pin	1	LAN, to UTR-211 Router	100BASE-T, 1000BASE-T	Starlink PoE

Antenna Specifications

Electronic Steerable Antenna

Start Frequency
10700 MHz
Stop Frequency
14500 MHz
Polarisation
Left Hand Circular (LHCP), Right Hand Circular (RHCP)
Input Impedance
50 Ω
Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	Azimuth	Elevation
10700 MHz	12700 MHz	30.4 dBi	3.5°	3.5°
14000 MHz	14500 MHz	31.8 dBi	2.8°	2.8°

Physical Specification

Subtype
Satellite Terminal
Min. Operating Temperature
-30 °C
Max. Operating Temperature
50 °C
Ingress Protection
IP54
Dimensions

513 × 303 × 544 mm
Weight
2.9 kg
Materials
Aluminium
Mounting
Starlink G3 34mm OD Spigot
Power Specifications
Max. Consumption
96 W
Typical Consumption
40 W
Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

