



Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

Inseego FW2000e 4G-5G Cat-22 Outdoor CPE, 2.5 Gbps

SKU: CPE-CL-00020 MPN: FW2000e

Description

USA-manufactured Inseego FW2000e is one of the biggest leaps in wireless technologies seen so far this decade. This 4G-5G Fixed Wireless unit provides multi-gigabit data speeds by combining both 4G and 5G carriers (EN-DC). Supporting the latest 5G NR standard along with an incredible Cat-22 4G LTE chipset this unit provides peak data rates of up to 2.5 Gb/s.

This unit totally simplifies the provision of high performance internet connectivity in regional and low signal areas. Simply connected by a single ethernet cable and powered by the included 802.3bt PoE injector, installation can be completed in a matter of minutes.

- Latest 5G NR release compatibility > 2.5 Gb/s
- 4G LTE Cat-22 Speeds up to 2562 Mb/s DL and 316 Mb/s
 UL
- 140 MHz 7C CA with 256QAM
- FDD+TDD LTE-A Pro including Supplemental Downlink (SDL) bands

Operating on all major 4G and 5G bands throughout Australia, Europe, United States, and abroad this unit stands ready to deliver multi ...

Read More

The FW2000e is a genuine disruptor, representing a total change to the way regional internet access and temporary site communications are deployed. Utilising the Inseego Connect platform, all device deployments can be centrally managed through a single pane-of-glass.

Powered by Inseego FW2000e, the unit is equipped with a dual mode 4G LTE-A Pro and 5G NR Snapdragon X55 chipset supporting 4T4R multi-antenna technology. Its integrated 4x4 MIMO antenna system provides high gain (up to 14 dBi) on all sub-6 GHz bands.

As a dual-sim redundant, IP67 weatherproof device that supports temperature extremes, this unit is ideal for enterprise and industrial customers demanding high data rates with high reliability.



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...



Network Interfaces

Wireless Interfaces Cellular Module Technologies: 4G LTE, 5G NR Chipset/Module: Snapdragon X55 4G LTE Specifications



| MIMO: | 4x4 MIMO | DL Category: | Cat 22 |
|---------------|----------|----------------------|--------|
| LTE Bands: | B1 | UL Category: | Cat 20 |
| B2 | ı | Carrier Aggregation: | 7C CA |
| , B3 | | | |
| , B4 | | | |
| , B5 | | | |
| , B7 | | | |
| , B8 | | | |
| , B12 | | | |
| , B13 | | | |
| , B14 | | | |
| , B17 | | | |
| B20 | | | |
| , B25 | | | |
| , B26 | | | |
| , B28 | | | |
| , B29 | | | |
| , , B30 | | | |
| , , B32 | | | |
| , | | | |
| B38 | | | |
| B39 | | | |
| B40 , | | | |
| B41 , | | | |
| B42 | | | |
| B43 | | | |

5G Sub-6 GHz Specifications 5G Bands: MIMO: 4x4 MIMO n1 n2 n3 n5 n7 n12 n20 n25 n28 n38 n40 n41 n48 n66 n71 n77 n78 SIM Cards Quantity SIM Type 2 Nano SIM (4FF)

Bluetooth Interface

Protocol: Bluetooth 4.0 Power Class:

Ethernet Interfaces

Interface Quantity Function Signalling PoE Input

RJ45 Copper 1 LAN 100BASE-T, 1000BASE-T 802.3bt Type 3 PoE++

Antenna Specifications

| Start Frequency: | 600 MHz | Polarisation: | Dual Slant ±45° |
|------------------|----------|------------------|-----------------|
| Stop Frequency: | 4200 MHz | Input Impedance: | 50 |

Class 2

Frequency Test Data

| Start Freq. | Stop Freq. | Peak Gain |
|-------------|------------|-----------|
| 600 MHz | 960 MHz | 4 dBi |
| 960 MHz | 1695 MHz | 5 dBi |
| 1695 MHz | 2700 MHz | 12 dBi |
| 3300 MHz | 4200 MHz | 14 dBi |

Physical Specification

| Subtype: | Cellular Modem | Dimensions: | 400 × 71.7 × 430 mm |
|-----------------------------|----------------|----------------------------|---------------------|
| Min. Operating Temperature: | -30 °C | Weight: | 4.22 kg |
| Max. Operating Temperature: | 70 °C | Compliance/Certifications: | CE |
| Ingress Protection: | IP67 | RCM | 1 |
| | | , RoHS | |

Power Specifications

Max. Consumption: 90 W Typical Consumption: 9 W

Power Options: Power over Ethernet

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

