

Cellferno M1200 4G Outdoor CPE - 600 Mbps LTE

SKU: CPE-CL-00011

MPN: M1200

Description

Designed to provide near-gigabit wireless broadband, this all-outdoor modem incorporates the latest Sierra Wireless Cat-12 4G module and an AAS MIMO antenna system integrated with an IP66 weatherproof enclosure.

- Cat-12 – Speeds up to 600 Mb/s
- 60 MHz 3C CA with 256QAM
- FDD+TDD LTE-A Pro including Supplemental Downlink (SDL) bands
- Backwards compatible with legacy 3G networks

The M1200 is equipped with an LTE-Advanced Pro Cat-12 chipset supporting 4T2R multi-antenna technology. Operating on all major 4G bands throughout Australia, Europe, United States, and abroad this unit stands ready to deliver near-gigabit wireless access to areas beyond the ordinary footprint of high speed 4G networks.

Read More

Cellferno's M1200 Active Antenna is a true disruptor, eliminating the need for complicated antennas and cables. Plug-and-play using an ordinary ethernet cable, the unit can be self-installed in a matter of minutes. The unit is one of few capable of realising the true power of LTE-A Pro and remains to date the only Cat-12 ODU on the market.

Being able to stand up to harsh Australian conditions was at the front of mind when this product was designed, operating in temperatures up to 65°C, rugged stainless steel mount, IP66



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

Network Interfaces

Wireless Interfaces

Cellular Module

Technologies:

3G UMTS, 4G LTE

Chipset/Module:

Sierra Wireless EM7565

4G LTE Specifications

MIMO:	2x2 MIMO	DL Category:	Cat 12
LTE Bands:	B1	UL Category:	Cat 13
B2	,	Carrier Aggregation:	2C CA
,			
B3			
,			
B4			
,			
B5			
,			
B7			
,			
B8			
,			
B9			
,			
B12			
,			
B13			
,			
B18			
,			
B19			
,			
B20			
,			
B26			
,			
B28			
,			
B29			
,			
B30			
,			
B40			
,			
B41			
,			
B42			
,			
B43			
,			
B46			
,			
B48			
,			
B66			

SIM Cards

Quantity	SIM Type
1	Standard SIM (2FF)

Ethernet Interfaces

Interface	Quantity	Function	Signalling	PoE Input
RJ45 Copper	1	LAN	100BASE-T, 1000BASE-T	Passive PoE

Antenna Specifications

Start Frequency: 698 MHz Polarisation: Dual Slant $\pm 45^\circ$

Stop Frequency: 6000 MHz Input Impedance: 50

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR	Azimuth	Elevation	F/B Ratio
698 MHz	960 MHz	5 dBi	< 2:1	90°	90°	> 10 dB
1695 MHz	2200 MHz	8 dBi	< 2:1	70°	70°	> 10 dB
2200 MHz	2700 MHz	10 dBi	< 2:1	50°	50°	> 10 dB


Physical Specification

Subtype: Cellular Modem	Dimensions: 247 × 247 × 107 mm
Min. Operating Temperature: -40 °C	Weight: 1.5 kg
Max. Operating Temperature: 65 °C	Materials: Aluminium Die Cast
Ingress Protection: IP67	Mounting: Pole Clamp 25 to 63 mm
	Compliance/Certifications: R-NZ
	RCM

Power Specifications

Power Options: Power over Ethernet

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

