

Cambium ePMP 3000 4x4 MU-MIMO 5 GHz Access Point, 1.2 Gbps

SKU: WIF-CB-00043

MPN: C050910A801A

Description

Cambium's ePMP 3000 is a third generation multipoint wireless radio designed as an economical solution for point-to-multipoint WISP applications.

The ePMP 3000 carries on the interference tolerance mechanisms from ePMP 2000 but adds the power of Multi-User MIMO (MU-MIMO). The ePMP 3000 is a 4x4 MU-MIMO access point that can double the throughput at the sector level with the same channel bandwidth by serving two subscribers at the same time.


Coupling its 80 MHz channel width with a peak modulation scheme of 256QAM the ePMP 3000 access point can provide up to 1.2 Gb/s of aggregate L1 throughput, and supporting data rates as high as 600 Mb/s to a single subscriber module. The system supports up to 120 subscribers per sector.

This system is designed for connection to Force 300 subscriber modules.

The radio is listed separately from compatible antennas, allowing the unit to be paired with antennas of any design.

[Read More](#)

The ePMP 3000 continues interference mitigation techniques with support of the beam steering antenna for uplink, dynamic filtering for neighboring channel interference, and the robust



Cambium Networks

Cambium Networks enables service providers; enterprises; governmental and military agencies; oil, gas and utility companies; Internet service providers; and public safety organizations to build powerful communications networks, reach users from 200 kilometers across mountain tops down to their devices, and intelligently manage their business Wi-Fi infrastructure through end-to-end network ...

[Read More](#)

Network Interfaces

Wireless Interfaces

Topology:	Point-to-Multipoint (P2MP)	Max. Clients:	120				
Max. Throughput:	1200 Mb/s	Aggregate Channel Width:	80 MHz				
Encryption:	AES-128						
Transmit Power:	32 dBm	Receive Sensitivity:	-92 dBm				
Beamforming:	2DBF						
Wireless Bands	Path Mode	Start Frequency	Stop Frequency	MIMO	Channel Width	Modulation	Max. Data Rate
5 GHz	TDD	4910 MHz	5970 MHz	4x4 MIMO	80 MHz	256QAM	1200 Mb/s

RF Connections

RF Connector Function	Quantity	RF Interface	Notes
Wireless Link	4	SMA Female	Standard Antenna Connection
Wireless Link	2	RP-SMA Female	Beamforming Antenna Connection
GNSS	1	SMA Female	GPS Antenna (Supplied)

Ethernet Interfaces

Interface	Quantity	Function	Signalling	PoE Input
RJ45 Copper	1	Data + PoE Input	100BASE-T, 1000BASE-T	802.3at PoE+

Physical Specification

Min. Operating Temperature:	-30 °C	Dimensions:	45 x 137 x 330 mm
Max. Operating Temperature:	55 °C	Weight:	1.3 kg
Ingress Protection:	IP55	Materials:	Plastic
		Compliance/Certifications:	R-NZ
		RCM	,

Power Specifications

Max. Consumption:	25 W
Power Options:	Power over Ethernet

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

