

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

G41 Repeater Subassembly for 24 Vdc Integrated Platforms with Winch-Up Masts

MPN: RFSA-G41-24-WU

Description

This is a 4G repeater subassembly that can be installed in an Integrated Platform alongside a 24 Vdc Power System and Winch-Up Mast. The system uses a Cel-Fi G41 repeater, which is designed to be used while stationary. The Low-Band panel antenna provides a beam of coverage typically out to about 400 metres (input signal quality dependent).

It typically forms part of a BOM for a 4G Repeater Trailer or Skid. It contains all components necessary to "bolt-on" inside the electrical enclosure and onto the mast. This subassembly is designed for Winch-Up masts that have coaxial cables preinstalled inside the thermoformed harness.

This subassembly is designed for 24 Vdc power systems, and has a DC-DC converter to step the voltage back to 12 Vdc for the Cel-Fi repeater.

An Isolation Screen should ideally be installed to ensure maximum RF performance.





Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

Nextivity Cel-Fi GO G41-JE Cellular 4G-5G Stationary Repeater



Simultaneous Bands:	2	Relay Bandwidth:	40.00 MHz
Downlink Max. Gain:	100 dB	Uplink Max. Gain:	100 dB
Supported Technologies:	3G UMTS, 4G LTE, 5G NR		
Dimensions:	260 × 107 × 63 mm	Min. Operating	0 °C
Weight:	2 kg	Temperature: Max. Operating	40 °C
		Temperature:	

Powertec 4G Low Band H-Pol Panel Antenna, 698 to 960 MHz, 4.3-10 Female



Start Frequency:	698 MHz	Polarisation:	Horizontal (H)
Stop Frequency:	960 MHz	Input Impedance:	50
Max. Input Power:	100 W		
Subtype:	Panel / Sector	Dimensions:	500 x 280 x 125
MIMO:	1x1 SISO		Polyvinyl Chloride
Min. Operating	-40 °C		(PVC)
Temperature:	70 °C	Mounting:	Pole Clamp 30 to 52 mm
Max. Operating			
Temperature:		Weight:	3 kg

ZCG Low Band High Gain Yagi Antenna, 700 to 890 MHz, 15 dBi, 4.3-10 Female Start Frequency: 698 MHz Polarisation: Linear Stop Frequency: 890 MHz Input Impedance: 50 Max. Input Power: 100 W Subtype: Yagi Dimensions: 1550 x 25 x 235 MIMO: 1x1 SISO Materials: Aluminium -40 °C Weight: Min. Operating 0.75 kg Temperature: 85 °C Max. Operating Temperature:

Subcomponents

Quantity	Subcomponent
1	Nextivity Cel-Fi GO G41-JE Cellular 4G-5G Stationary Repeater
1	Powertec 4G Low Band H-Pol Panel Antenna, 698 to 960 MHz, 4.3-10 Female
1	ZCG Low Band High Gain Yagi Antenna, 700 to 890 MHz, 15 dBi, 4.3-10 Female
1	
4	4.3-10 Male Connector for L-240 Coaxial Cable
1	PSF-402 Patch Cable 4.3-10 Male to SMA Male 1m
1	PSF-402 Patch cable 4.3-10 Male to SMA Male 50cm
1	Victron Orion-Tr 24/12-5 (60W) DC-DC Converter

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

