

# Taoglas MA241 Genesis 2x2 MIMO 4G Adhesive Antenna

SKU

ANT-TG-00004

MPN

MA241.BI.001

## Description

The MA241 Genesis antenna is an omni-directional, fully IP67 waterproof external M2M antenna for use in telematics, transportation and remote monitoring applications. It is designed to be mounted directly on glass or plastic in the interior of vehicles.

This unique antenna delivers powerful MIMO antenna technology for worldwide 4G LTE bands between 700 and 2700 MHz. It enables designers to use only one antenna that covers all common frequencies for LTE globally.

4G wireless applications demand high speed data uplink and downlink. High efficiency and high gain MIMO antennas are necessary to achieve the required signal to noise ratio and throughput required to solve these challenges. Taoglas also takes care to have high isolation between the two MIMO antennas to prevent self-interference. Low loss cables are used to keep efficiency high over long cable lengths. In contrast, smaller MIMO antennas with poorer quality thinner cables will have ...

[Read More](#)

The Taoglas MA241 Genesis 2x2 MIMO 4G Adhesive Antenna is an advanced, omni-directional solution for telematics, transportation, and remote monitoring applications. With an IP67 waterproof rating, this external antenna is ideal for vehicle interiors, adhering directly to glass or plastic surfaces. It supports worldwide 4G LTE bands from 700 to 2700 MHz, enabling seamless global connectivity with a single antenna.

Designed for high-performance applications, the MA241 utilises MIMO technology to enhance data speeds and improve signal quality, crucial for robust 4G

networks. It features high efficiency and gain to meet demanding signal requirements, and the high isolation between MIMO elements minimises self-interference, ensuring reliable operation. Equipped with low-loss cables, it maintains high efficiency over extended lengths, unlike smaller, less effective antennas.

Constructed from durable ABS plastic and polycarbonate, the antenna...

[Read More](#)



[Taoglas](#)

Taoglas provides a comprehensive range of external, embedded and base station antenna solutions for M2M applications such as Telematics / Automotive, Smart-Grid, Metering / Telemetry, Home Automation, Remote Monitoring and Medical applications.

Taoglas' cross-cultural business-solutions approach means research, design, production and customer support services are based at our world-class technology ...

## RF Specification

Start Frequency

698 MHz

Stop Frequency

2700 MHz

Max. Input Power

5 W

Polarisation

[Linear](#)

Input Impedance

50  $\Omega$

RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
-------	--------------	------------	--------------	--------

2	<a href="#">SMA Male</a>	<a href="#">Straight</a>	<a href="#">L-200</a>	2000 mm
---	--------------------------	--------------------------	-----------------------	---------

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR	Avg. Gain	Efficiency
-------------	------------	-----------	------	-----------	------------

698 MHz	803 MHz	3.1 dBi	< 3.5:1	-1.96 dBi	64%
---------	---------	---------	---------	-----------	-----

824 MHz	894 MHz	1 dBi	< 3.5:1	-3.76 dBi	42%
---------	---------	-------	---------	-----------	-----

880 MHz	960 MHz	-0.7 dBi	< 3.5:1	-5.35 dBi	29%
---------	---------	----------	---------	-----------	-----

1710 MHz	1880 MHz	2.5 dBi	< 3.5:1	-2.3 dBi	60%
----------	----------	---------	---------	----------	-----

1850 MHz	1990 MHz	-0.3 dBi	< 3.5:1	-4.8 dBi	34%
----------	----------	----------	---------	----------	-----

1920 MHz	2170 MHz	-1.5 dBi	< 3.5:1	-5.7 dBi	27%
----------	----------	----------	---------	----------	-----

2390 MHz	2690 MHz	3.8 dBi	< 3.5:1	-3 dBi	50%
----------	----------	---------	---------	--------	-----

3410 MHz	3490 MHz	3.5 dBi	< 2:1	-5.7 dBi	29%
----------	----------	---------	-------	----------	-----

## Physical Specification

Subtype

## [Adhesive Patch](#)

Input Ports

2

MIMO

### [2x2 MIMO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

85 °C

Dimensions

206 x 12.4 x 68

Ingress Protection

### [IP67](#)

Materials

[ABS Plastic](#), [Polycarbonate \(PC\)](#)

Mounting

### [Adhesive](#)

Weight

0.21 kg

Compliance/Certifications

ISO 9001 Quality Management

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

