

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Taoglas MA251 Sentinel 2x2 MIMO 4G Adhesive Antenna

SKU
ANT-TG-00010
MPN
MA251.A.BI.001

Description

The MA251 Sentinel 2-in-1 adhesive mount 4G 2x2 LTE MIMO antenna is an omnidirectional, fully IP67 waterproof external IoT/M2M antenna for use in telematics, transportation and remote monitoring applications worldwide. It is designed to be mounted directly on glass or plastic in the interior of vehicles.

It is the smallest high performance solution in the market, 50% smaller than the previous generation, with higher efficiency and wider bandwidth to cover emerging LTE bands. Its performance is comparable with much larger permanent roof mount antennas and now offers a convenient and economical alternative in-cabin mounting solution.

It is mounted via high quality, first tier automotive approved, 3M adhesive. In-house world leading dielectric ceramic antenna technology inside allows for smaller size antennas without loss in efficiency. It delivers powerful 2x2 MIMO antenna technology for worldwide 4G LTE bands between 700 and 2600 MHz ...

[Read More](#)

The Taoglas MA251 Sentinel 2x2 MIMO 4G Adhesive Antenna offers a compact, high-performance solution for telematics, transportation, and remote monitoring applications. Designed for easy interior mounting on vehicle glass or plastic surfaces, this antenna is 50% smaller than previous models yet delivers superior efficiency and bandwidth, covering emerging LTE bands. Its omnidirectional design and IP67 waterproof rating ensure reliable performance in diverse environments.

The MA251 utilises advanced dielectric ceramic technology, enabling a streamlined form without compromising efficiency. Supporting worldwide 4G LTE bands between 700 and 2600 MHz, it also accommodates fallback to common 3G and 2G frequencies, making it versatile for global deployments. The antenna's 2x2 MIMO configuration enhances data transmission with high speed and low latency, essential for today's demanding 4G wireless applications. High isolation between MIMO...

[Read More](#)



[Taoglas](#)

Taoglas provides a comprehensive range of external, embedded and base station antenna solutions for M2M applications such as Telematics / Automotive, Smart-Grid, Metering / Telemetry, Home Automation, Remote Monitoring and Medical applications.

Taoglas' cross-cultural business-solutions approach means research, design, production and customer support services are based at our world-class technology ...

RF Specification

Start Frequency

698 MHz

Stop Frequency

2690 MHz

Max. Input Power

5 W

Polarisation

[Linear](#)

Input Impedance

50 Ω

RF Connectors

Ports RF Interface Body Shape Cable Series Length

2 [SMA Male](#) [Straight](#) [L-200](#) 2000 mm

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR	Avg. Gain	Efficiency	Inter-Port Iso.
698 MHz	803 MHz	0.7 dBi	< 3.5:1	-4.3 dBi	37%	> 10 dB
824 MHz	894 MHz	1.3 dBi	< 3.5:1	-2.8 dBi	52%	> 10 dB
880 MHz	960 MHz	2.1 dBi	< 3.5:1	-2.8 dBi	53%	> 10 dB
1710 MHz	1880 MHz	3.8 dBi	< 3.5:1	-2.6 dBi	60%	> 20 dB
1850 MHz	1990 MHz	3.8 dBi	< 3.5:1	-2.1 dBi	62%	> 20 dB
1920 MHz	2170 MHz	3.4 dBi	< 3.5:1	-2.7 dBi	55%	> 20 dB
2490 MHz	2690 MHz	3.1 dBi	< 3.5:1	-3.5 dBi	45%	> 20 dB

Physical Specification

Subtype

[Adhesive Patch](#)

Input Ports

2

MIMO

[2x2 MIMO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

85 °C

Dimensions

76 x 139 x 14

Ingress Protection

[IP67](#)

Materials

[ABS Plastic](#)

Mounting

[Adhesive](#)

Weight

0.24 kg

Compliance/Certifications

ISO 9001 Quality Management

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

