

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Powertec 5G 4x4 MIMO Panel Antenna, 3300 to 3800 MHz, 4.3-10 Female

SKU
ANT-PT-00014
MPN
4XPA-3338-14.432
Barcode
9337692003738

Description

4XPA-3338-14 is a commercial grade 4x4 MIMO antenna designed for use on 5G networks. Providing a nominal peak gain of 14 dBi across 3300 to 3800 MHz the antenna is an ideal solution for gigabit wireless access over the 5G n78 (3500 MHz) band.

The antenna's patch array design provides a slim unobtrusive form factor, while maintaining exceptional isolation, null fill, and discrimination characteristics.

Four 4.3-10 Female bulkhead connectors (or N Female on request) exit the rear of the antenna, allowing direct connection of cables to the patch array.

Powertec's 4XPA-3338-14 antenna is designed specifically for the 5G 3.5 GHz C-Band, which is the most dominantly deployed 5G network frequency. The antenna has been designed for testing of 5G networks, and for long range 5G connectivity.

[Read More](#)





Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

Start Frequency

3300 MHz

Stop Frequency

3800 MHz

Max. Input Power

10 W

Polarisation

Dual Slant $\pm 45^\circ$

Input Impedance

50 Ω

RF Connectors

Ports RF Interface Body Shape

4 4.3-10 Female Straight

Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR	Azimuth	Elevation	F/B Ratio	Inter-Port Iso.	Cross-Polar Iso.
3300 MHz	3600 MHz	13.8 dBi	< 2:1	35°	35°	> 24 dB	> 25 dB	> 15 dB

Start Freq.	Stop Freq.	Peak Gain	VSWR	Azimuth	Elevation	F/B Ratio	Inter-Port Iso.	Cross-Polar Iso.
3600 MHz	3800 MHz	14.3 dBi	< 2:1	30°	30°	> 25 dB	> 25 dB	> 15 dB

Physical Specification

Subtype

[Panel / Sector](#)

Input Ports

4

MIMO

[4x4 MIMO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

65 °C

Dimensions

250 x 250 x 25

Materials

[ABS Plastic](#), [Aluminium](#)

Mounting

[Pole Clamp 25 to 52 mm ø](#)

Weight

2.5 kg

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

