

Page



Powertec Wireless Technology
ABN: 42 082 948 463
PO Box 1034, Ashmore City
Queensland, Australia, 4214
sales@powertec.com.au
1300 769 378

Taoglas TLS.01 Shockwave Wideband 4G-5G Bulkhead Antenna

SKU
ANT-TG-00014
MPN
TLS.01.1F21

Description

The Shockwave TLS.01.1F21 is a permanent mount, waterproof, external 4G 5G antenna operating across the full wideband 600 to 6000 MHz frequency range with an N type Female bulkhead connector. It has been designed to be used on a Ground Plane.

This antenna has superior performance over wide-bands compared to traditional whip antennas. Up to 90% efficiency and with a minimum 2.3dBi peak gain over all cellular bands result when mounted on a 300 x 300 mm ground plane. Stable radiation patterns over low angles provides consistent gain in the horizontal plane, meaning that it is especially suitable for cellular applications.

A unique indent tab on the base of the antenna allows a wrench to be used to solidly lock the antenna on top of its mounting location, where an N type female connector juts out from a metal panel. Waterproof O-rings around the bottom base prevent water from leaking under the antenna.

The TLS.01 antenna is IP67 waterproof and ...

[Read More](#)

The Taoglas TLS.01 Shockwave Wideband Antenna, model TLS.01.1F21, is a robust 4G/5G external antenna designed for ground plane mounting. Its wide frequency range of 600 to 6000 MHz ensures superior performance across all cellular bands, making it ideal for applications like 5G, 4G, Cat-M, and NB-IoT. This antenna achieves up to 90% efficiency with a minimum 2.3dBi peak gain, ensuring stable horizontal radiation patterns for consistent cellular connectivity.

A key feature is its IP67/IP69K waterproof rating, which guarantees durability in harsh outdoor environments and resistance to high-pressure cleaning. The antenna's secure bulkhead mount incorporates a unique indent tab for easy installation, and an N type female connector ensures reliable connections.

Constructed from ABS plastic and zinc alloy, the antenna measures 79.4 mm in height and 42 mm in diameter, weighing just 0.13 kg. It operates efficiently from -40 °C to 85 °C and...

[Read More](#)



Taoglas

Taoglas provides a comprehensive range of external, embedded and base station antenna solutions for M2M applications such as Telematics / Automotive, Smart-Grid, Metering / Telemetry, Home Automation, Remote Monitoring and Medical applications.

Taoglas' cross-cultural business-solutions approach means research, design, production and customer support services are based at our world-class technology ...

RF Specification

Start Frequency

600 MHz

Stop Frequency

6000 MHz

Max. Input Power

100 W

Polarisation

[Vertical \(V\)](#)

Input Impedance

50 Ω

RF Connectors

Ports RF Interface Body Shape

1 [N Female](#) [Straight](#)

Frequency Test Data

Start Freq. Stop Freq. Peak Gain VSWR Avg. Gain Efficiency

617 MHz	698 MHz	-1 dBi	< 4:1	-3.2 dBi	47%
698 MHz	806 MHz	3.1 dBi	< 1.5:1	-0.2 dBi	95%
824 MHz	960 MHz	3.2 dBi	< 2:1	-0.7 dBi	85%
1427 MHz	1518 MHz	2.9 dBi	< 2.5:1	-1.4 dBi	72%
1710 MHz	2200 MHz	2.7 dBi	< 2.5:1	-1.8 dBi	66%
2300 MHz	2690 MHz	3.4 dBi	< 2.5:1	-2 dBi	63%
3300 MHz	3800 MHz	2.5 dBi	< 3:1	-4.1 dBi	41%
5150 MHz	5925 MHz	5.3 dBi	< 3:1	-3.4 dBi	46%

Physical Specification

Subtype

[Fin / Stud / Combo](#)

Input Ports

1

MIMO

[1x1 SISO](#)

Min. Operating Temperature

-40 °C

Max. Operating Temperature

85 °C

Dimensions

79.4 x 42 (H x Dia)

Ingress Protection

[IP69K](#)

Materials

[ABS Plastic](#), [Zinc Alloy](#)

Mounting

[M14 Stud](#)

Weight

0.13 kg

Compliance/Certifications

ISO 9001 Quality Management

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

