

---

# Taoglas G30 Olympian Wideband 4G / IoT Stud Antenna

SKU: ANT-TG-00002

MPN: G30.B.108111

## Description

---

The G30 Olympian is a high performance screw mount wide-band cellular antenna for external use on vehicles and outdoor assets worldwide. Omnidirectional high gain and high efficiency across all bands ensures constant reception and transmission. This is vital for today's high data bandwidth applications in video and mobile broadband.

Durable UV resistant ABS housing is resistant to vandalism and direct attack. At only 48 mm height it complies with the latest EU height restrictions directives for roof-mounted objects. This antenna is mounted on metal and plastic structures and is locked from the inside of the structure by a nut. Adhesive foam at the base provides a watertight seal to the mounting structure. High quality waterproof and corrosion resistant Teflon jacket RG316 is used for the cable.

Two of these G30 separated at distance from each other are ideal for the latest LTE MIMO spatial diversity applications.

Customised cable length ...

Read More

The Taoglas G30 Olympian Wideband 4G / IoT Stud Antenna (SKU: ANT-TG-00002) is a high-performance, omnidirectional antenna designed for exterior installation on vehicles and outdoor assets. It offers reliable reception and transmission across all major cellular bands, making it ideal for high-bandwidth applications like video streaming and mobile broadband. Constructed with durable UV-resistant ABS housing, it withstands vandalism and adverse weather conditions, and complies with EU height restrictions at only 48 mm tall.

The G30's screw mount design ensures secure installation on both metal and plastic surfaces, with an internal nut for added stability and adhesive foam for a watertight seal. Its RG316 cable, featuring a Teflon jacket, is both waterproof and corrosion-resistant. The antenna is IP67 rated for waterproofing, making it suitable for demanding environmental conditions.



### Taoglas



## RF Specification

Taoglas provides a comprehensive range of external, embedded and base station antenna solutions for M2M applications such as Telematics / Automotive, Smart-Grid, Metering / Telemetry, Home Automation, Remote Monitoring and Medical applications.

Taoglas' cross-cultural business-solutions approach means research, design, production and customer support services are based at our world-class technology ...

Start Frequency:	698 MHz	Polarisation:	Vertical (V)
------------------	---------	---------------	--------------

Stop Frequency:	2800 MHz	Input Impedance:	50
-----------------	----------	------------------	----

Max. Input Power:	5 W
-------------------	-----

#### RF Connectors

Ports	RF Interface	Body Shape	Cable Series	Length
1	SMA Male	Straight	RG-316	1000 mm

#### Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR	Avg. Gain	Efficiency
698 MHz	960 MHz	1.2 dBi	< 3:1	-4.5 dBi	40%
1710 MHz	2170 MHz	3.2 dBi	< 3:1	-2.5 dBi	55%
2300 MHz	2483 MHz	1.5 dBi	< 3:1	-4.5 dBi	38%
2500 MHz	2800 MHz	2.5 dBi	< 2:1	-4.5 dBi	40%

# Physical Specification

Subtype:	Fin / Stud / Combo	Dimensions:	48 x 50 (H x Dia)
Input Ports:	1	Ingress Protection:	IP67
MIMO:	1x1 SISO	Materials:	ABS Plastic
Min. Operating Temperature:	-40 °C	Mounting:	M12 Stud
Max. Operating Temperature:	85 °C	Weight:	0.07 kg
		Compliance/Certifications:	ISO 9001 Quality Management

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

