POWERTEC | DATASHEET | UNCONTROLLED WHEN PRINTED PUBLIC | July 31, 2025 19:14

Page



Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

Powertec Wideband 4G Magnetic Antenna, 700 to 2700 MHz, SMA Male

SKU ANT-EC-00001 MPN VMAG-6927-4.SA1 Barcode 9337692004421

Description

It's truly not often that an antenna surprises our team. Manufactured in Taiwan, this antenna provides true wideband operation across the full 3G and 4G range 700 to 2700 MHz. The antenna has been optimised for operation across the lower cellular band to provide best performance on 4G frequencies, including long range 700 MHz 4GX and 5G 850 MHz Telstra NR850.

The antenna provides a 5 dBi gain across the 700 to 900 MHz band, and 4 dBi gain across 1695 to 2700 MHz - a very difficult achievement for this design type.

During independent laboratory testing the antenna consistently demonstrated excellent performance. The antenna has a reasonably sturdy design and its thin visual profile goes unnoticed to the passer-by. The antenna is an ideal choice for IoT applications, such as NB-IoT and LTE-M.

- 5 dBi gain across lower bands 698 to 960 MHz
- 4 dBi gain across mid bands 1695 to 2700 MHz
- Ideal for IoT and industrial M2M applications, such as metering and monitoring
- True wideband 4G, covering the entire band with high radiated efficiency
- Ground plane dependent
- 3 metre RG-58 cable with an SMA Male connector





Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

Cable 1

Start Frequency 698 MHz Stop Frequency 2700 MHz Max. Input Power 50 W Polarisation Vertical (V) Input Impedance 50 Ω **RF** Connectors Ports RF Interface Body Shape Cable Series Length 1 SMA Male Straight **RG-58** 3000 mm Frequency Test Data Start Freq. Stop Freq. Peak Gain VSWR Elevation Efficiency 698 MHz 824 MHz 3.4 dBi < 1.9:1 90° 70% 824 MHz 960 MHz 4.99 dBi < 1.9:1 80° 68% < 2:1 80° 55% 1695 MHz 2200 MHz 4.3 dBi 2700 MHz 4.4 dBi < 2.8:1 80° 2200 MHz 40% **Polar Patterns** Start Frequency 698 MHz Stop Frequency 960 MHz

Azimuth Polar Plot



Elevation Polar Plot



Start Frequency 1710 MHz Stop Frequency 2700 MHz

Azimuth Polar Plot



Elevation Polar Plot



Physical Specification

Subtype Whip Input Ports 1 MIMO 1x1 SISO Min. Operating Temperature -30 °C Max. Operating Temperature 80 °C Dimensions 238 x 86 x 86 Materials Steel, Thermoplastic Elastomer (TPE) Mounting Magnetic Weight 0.48 kg Compliance/Certifications ISO 9001 Quality Management Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

