

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

# Powertec Wideband 4G-5G Hinged Antenna, 700 to 3800 MHz, SMA Male

SKU: ACC-PT-00391 MPN: ACC-PT-00391 Barcode: 9337692004568

### Description

The VHT-6938-2 is an economical terminal antenna covering a wide range of 4G LTE and 5G NR frequencies between 700 and 3800 MHz. Most notably the antenna covers all common 3G and 4G bands, along with n78 (3500 MHz) used in most 5G networks across the globe.

Designed for terminals and routers, the antenna offers an articulated SMA connector for flexible positioning and a sleek profile for low visual impact. The antenna demonstrates stable omnidirectional performance with 2 to 3 dBi gain across the bands.

#### Read More

This model of antenna is quickly being used as a drop-in replacement for older designs that aren't compatible with 5G. The unit is economically priced, with discount tiers at 100, 1000, and 5000 units, making it an exceptional choice for mass-deployment.





#### Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

## RF Specification

Start Frequency:	698 MHz	Polarisation:	Linear
Stop Frequency:	3800 MHz	Input Impedance:	50
Max. Input Power:	10 W		

### **RF Connectors**


PortsRF InterfaceBody Shape1SMA MaleStraight

### Frequency Test Data

Start Freq.	Stop Freq.	Peak Gain	VSWR
698 MHz	960 MHz	2 dBi	< 3:1
1695 MHz	2690 MHz	3 dBi	< 3:1
3300 MHz	3800 MHz	3 dBi	< 2.6:1

# **Physical Specification**

Subtype:	Hinged Terminal	Dimensions:	198 x 37.3 x 13
Input Ports:	1	Materials:	ABS Plastic, Thermoplastic
MIMO:	1x1 SISO		Elastomer (TPE)
Min. Operating Temperature:	-35 °C	Mounting:	Terminal / Device
		Weight:	0.04 kg
Max. Operating Temperature:	70 °C		



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

