

Superior Essex 04-001-55 Copper Cable, 4 Pair, 24 AWG BBD Category 5e, 304m Reel

SKU: ACC-SE-00001

MPN: 04-001-55

Description

EnduraGain® OSP Armored is an extremely tough category 5e Ethernet cable designed to operate in a wide range of industrial environments. The outdoor-rated cable is fully weatherproof, resistant to oils, and protected by two PE jackets separated by a corrugated Copper-Clad Steel armouring.

The cable consists of four balanced twisted pairs surrounded by Superior Essex PFM™ gel that does not drip or flow, even in cell tower applications at elevated temperatures.

The jacketed core is covered with dry block and a corrugated, copper-clad steel armour providing exceptional Alien Crosstalk (AXT) performance. The outer jacket is an OSP-grade black polyethylene for superior sunlight and abrasion resistance. This armoured design is suitable for the following deployments: duct, underground conduit, tower, lashed aerial, direct burial or open trench.

[Read More](#)

Superior's EnduraGain OSP Armoured cables are recommended by leading packet microwave radio vendors due to their extreme environmental handling and ability to be installed with direct burial in soil or concrete without the requirement for conduit, and hauled up communications towers without damage or dripping of waterproofing gel.

[Read More](#)



Superior Essex

Superior Essex International LP manufactures a broad portfolio of wire and cable products and accessories, including premises copper and optical fiber cables, Outside Plant (OSP) copper and fiber cables, Distributed Antenna Systems (DAS) cables and accessories that service the Enterprise, Commercial, Industrial, and Utility markets. Superior Essex practices a high level of environmental ...

Physical Specification

| | | | |
|---|----------------------------------|-----------------------------|--------|
| Subtype: | Cable Reel | Length: | 304 m |
| Weight: | 28 kg | | |
| Ethernet Category: | Cat5e | Min. Operating Temperature: | -40 °C |
| Shielding: | U/UTP | Max. Operating Temperature: | 75 °C |
| Colour: | Black | Weight (g/m): | 89 g |
| Environmental Suitability: | Aerial Use Chemical Resistant | | |
| Direct Burial Indoor Use Oil Resistant Outdoor Use UV-Resistant | | | |

Cable Layers

| Layer | Diameter | Materials |
|----------------------|----------|----------------------------|
| Waterproofing Gel | | Polymer Fiber Matrix (PFM) |
| Inner Conductor | 0.51 mm | Solid Copper |
| Conductor Insulation | | Polyolefin LSZH |
| Inner Jacket | | Polyethylene (PE) |
| Shielding | | Copper Clad Steel (CCS) |
| Outer Jacket | 9.10 mm | Polyethylene (PE) |

Downloadable Resources

SuperiorEssex-Enduragain-OSP_04-001-55_datasheet.pdf

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

