

Robustel R3000-L4L LITE Industrial Router, CAT-4, Dual-SIM, FE, RS232, RS485, USB

SKU: M2M-RO-00018
 MPN: R3000-L4L

Description

The Robustel Industrial Dual SIM Cellular VPN Router (R3000 Lite) is a rugged cellular router offering state-of-the-art mobile connectivity for machine to machine (M2M) applications.

R3000 Lite is a powerful router developed from RobustOS, a Robustel self-developed and Linux-based operating system which is designed to be used in Robustel devices. The RobustOS includes basic networking features and protocols providing customers with a very good user experience.

Meanwhile, Robustel offers a Software Development Kit (SDK) for partners and customers to allow additional customization by using C, Python or Java. It also provides rich Apps to meet fragmented IoT market demands.

DIN rail mount available.

A cost effective, industrial-grade VPN gateway designed for cost-sensitive M2M applications.

- Dual SIM redundancy for persistent 2G/3G/4G cellular network connections
- RobustOS + SDK + App
- IPsec/OpenVPN/GRE/L2TP/PPTP/DMVPN
- Management and maintenance via Web/CLI/SMS/SNMP/Robustlink Cloud



Robustel



Robustel are one of the world's leading manufacturers of industrial quality solutions for the IoT and M2M market. Robustel's portfolio of award-winning solutions are comprised of: Wireless Modems, Routers, Gateways, EDGE Computing, Cloud Software and End-to-End IoT solutions.

Wireless Interfaces

Founded in 2010 in Guangzhou, China - Robustel has been concentrating on producing the highest quality IoT products possible ...

Cellular Module

Technologies: 3G UMTS, 4G LTE

4G LTE Specifications

MIMO: 2x2 MIMO DL Category: Cat 4

LTE Bands: B1 UL Category: Cat 3

B3
,
B5
,
B7
,
B8
,
B28
,
B40

SIM Cards

Quantity	SIM Type
2	Standard SIM (2FF)

Modem RF Connectors

RF Connector Function	Quantity	RF Interface
Cellular	2	SMA Female

Ethernet Interfaces

Interface	Quantity	Function	Signalling
RJ45 Copper	1	LAN	100BASE-T

Physical Specification

Subtype:	Cellular Modem	Dimensions:	105 × 98 × 29.5 mm
Min. Operating Temperature:	-40 °C	Weight:	305 g
Max. Operating Temperature:	75 °C	Materials:	Aluminium
Ingress Protection:	IP30	Compliance/Certifications:	CE , , RCM , RoHS

IO Interfaces

IO Connector	Quantity	Notes
USB-A 2.0	1	
DE-9 Serial	1	1x RS-232 & 1x RS-485

Power Specifications

Power Options:	DC Power Input	Typical Consumption:	1.2 W
----------------	----------------	----------------------	-------

Power Interface

Power Connector	Nominal Voltage	Min. Input Voltage	Max. Input Voltage	Voltage Type
Terminal Block, 3-Position	12 V	9 V	36 V	DC

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

