
Telegartner Surge Protector, 4.3-10 Male to 4.3-10 Female, 3.8 GHz

SKU: ACC-TG-00008

MPN: 100025378

Description

Telegärtner's 4.3-10 Male to 4.3-10 Female Coaxial Surge Protector has been engineered to provide superior protection for high-frequency applications, extending up to 3.8 GHz. This makes it particularly suitable for the latest 5G networks and other advanced communication systems. Utilising a Gas Discharge Tube (GDT), this surge protector ensures the safeguarding of sensitive electronic equipment from high voltage surges.

- Interface: 4.3-10 Male to 4.3-10 Female
- Frequency Range: Operates up to 3.8 GHz, making it ideal for 5G and other high-frequency applications
- Surge Protection: Employs a Gas Discharge Tube (GDT) capable of handling high discharge currents up to 40 kA (8/20 impulse)
- Design: Robust and reliable design, ensuring minimal signal loss and maintaining excellent return loss values at high frequencies
- Replaceable GDT: The gas discharge tube is replaceable, allowing for easy maintenance and extended product life



The Telegärtner Surge Protector (SKU: ACC-TG-00008) is a high-performance RF surge protector designed for 4.3-10 Male to 4.3-10 Female connections, supporting frequencies up to 3.8 GHz. This makes it ideal for 5G networks and advanced communication systems. It utilises a Gas Discharge Tube (GDT) to protect sensitive electronic equipment from high voltage surges, with a discharge capacity of up to 40 kA (8/20 impulse).

Engineered with a robust design, this surge protector ensures minimal signal loss and excellent return loss values at high frequencies. The replaceable GDT allows for easy maintenance and extended lifespan. Constructed from quality materials including lead-brass alloy (CuZn39Pb3) and beryllium copper, it offers reliable performance in challenging environments with an IP67 rating, functioning effectively between -40 °C and 85 °C.

The surge protector maintains a VSWR of $\leq 1.25:1$ at 2700 MHz with a return loss of ≤ 30.00 dB and...

Read More

RF Connector Interface

Telegärtner



RF Interface

As family-owned company the Telegärtner Group has developed to an international network of affiliated companies

4.3-10 Male

Body Shape

Straight

Mounting

Free Hanging

4.3-10 Female

Straight

Free Hanging

Since the company was set up in 1945 Telegärtner has seen steady growth and has continually expanded ...

RF Specification

Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	3.8 GHz	Impulse Discharge:	10 x 15 kA (8/20 s)
Spark-over Voltage:	75 V	Inner Contact Resistance:	≤ 2 mΩ
		Outer Contact Resistance:	≤ 1 mΩ


VSWR Measurement

Frequency	Return Loss	Insertion Loss
2700 MHz	≤ 30 dB	0.1 dB
3800 MHz	≤ 20 dB	0.25 dB

Physical Specification

Body Material:	Lead-Brass Alloy (CuZn39Pb3)	Contact Material:	Beryllium Copper, Lead-Brass Alloy (CuZn39Pb3)
Body Plating:	CuSnZn3	Contact Plating:	Copper-Silver Alloy (Cu2Ag5 / Cu2Ag3)
Insulator Material:	PTFE / Teflon	Min. Operating Temperature:	-40 °C
Dimensions:	74 x 25 x 28.6	Max. Operating Temperature:	85 °C
Compliance/Certifications:	ISO 9001 Quality Management	Mating Cycles:	> 100
RoHS		Ingress Protection:	IP67

Drawing



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

