POWERTEC | DATASHEET | UNCONTROLLED WHEN PRINTED PUBLIC | August 1, 2025 04:41

Page



Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

Telegartner Surge Protector, 4.3-10 Male to 4.3-10 Female, 3.8 GHz

SKU ACC-TG-00008 MPN 100025378

Description

Telegärtner's 4.3-10 Male to 4.3-10 Female Coaxial Surge Protector has been engineered to provide superior protection for high-frequency applications, extending up to 3.8 GHz. This makes it particularly suitable for the latest 5G networks and other advanced communication systems. Utilising a Gas Discharge Tube (GDT), this surge protector ensures the safeguarding of sensitive electronic equipment from high voltage surges.

- Interface: 4.3-10 Male to 4.3-10 Female
- Frequency Range: Operates up to 3.8 GHz, making it ideal for 5G and other high-frequency applications
- Surge Protection: Employs a Gas Discharge Tube (GDT) capable of handling high discharge currents up to 40 kA (8/20 impulse)
- Design: Robust and reliable design, ensuring minimal signal loss and maintaining excellent return loss values at high frequencies
- Replaceable GDT: The gas discharge tube is replaceable, allowing for easy maintenance and extended product life

The Telegärtner Surge Protector (SKU: ACC-TG-00008) is a high-performance RF surge protector designed for 4.3-10 Male to 4.3-10 Female connections, supporting frequencies up to 3.8 GHz. This makes it ideal for 5G networks and advanced communication systems. It utilises a Gas Discharge Tube (GDT) to protect sensitive electronic equipment from high voltage surges, with a discharge capacity of up to 40 kA (8/20 impulse).

Engineered with a robust design, this surge protector ensures minimal signal loss and excellent return loss values at high frequencies. The replaceable GDT allows for easy maintenance and extended lifespan. Constructed from quality materials including lead-brass alloy (CuZn39Pb3) and beryllium copper, it offers reliable performance in challenging environments with an IP67 rating, functioning effectively between -40 °C and 85 °C.

The surge protector maintains a VSWR of \leq 1.25:1 at 2700 MHz with a return loss of \leq 30.00 dB and...

Read More





Telegärtner

As family-owned company the Telegärtner Group has developed to an international network of affiliated companies specialising in intermediate and end products for telecommunications and data communications for customers with the most exacting demands for high-tech applications over the last 70 years.

Since the company was set up in 1945 Telegärtner has seen steady growth and has continually expanded ...

RF Connector Interface

RF Interface Body Shape Mounting4.3-10 MaleStraight4.3-10 Female StraightFree HangingFree HangingFree Hanging

RF Specification

Start Frequency 0 GHz **Stop Frequency** 3.8 GHz Spark-over Voltage 75 V Input Impedance 50 Ω Impulse Discharge 10 x 15 kA (8/20µs) Inner Contact Resistance $\leq 2 \text{ m}\Omega$ **Outer Contact Resistance** $\leq 1 \text{ m}\Omega$ **VSWR** Measurement **Frequency Return Loss Insertion Loss**

2700 MHz \leq 30 dB0.1 dB3800 MHz \leq 20 dB0.25 dB

Physical Specification

Body Material Lead-Brass Alloy (CuZn39Pb3) Body Plating CuSnZn3 Insulator Material PTFE / Teflon Dimensions 74 x 25 x 28.6 Compliance/Certifications

ISO 9001 Quality Management

RoHS Contact Material Beryllium Copper, Lead-Brass Alloy (CuZn39Pb3) Contact Plating Copper-Silver Alloy (Cu2Ag5 / Cu2Ag3) Min. Operating Temperature -40 °C Max. Operating Temperature 85 °C Mating Cycles > 100 Ingress Protection IP67





Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE

INFORMATION.

