

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

## N Female Connector for L-400 Coaxial Cable

SKU: ACC-PT-00031 MPN: N2-C-L40

Barcode: 9337692003295

#### Description

The N Female Connector for L-400 Coaxial Cable, part number N2-C-L40, is a high-quality RF connector crafted by Powertec. Designed for optimal performance, it features a straight body and free-hanging mounting style, perfectly suited for L-400 cable types using a cable crimp attachment. Constructed from nickel-plated brass with gold-plated brass contacts, this connector ensures reliable conductivity and durability. The PTFE/Teflon insulator enhances electrical insulation, providing a robust solution for various applications.

This connector supports over 500 mating cycles and operates within a temperature range of -55 °C to 165 °C. It offers an operating frequency range from 0 to 6.0 GHz and maintains an input impedance of 50  $\Omega$ . With an insulation resistance of  $\geq$  5000 m $\Omega$  and RF operating voltage of  $\leq$  1000 Vrms, it delivers dependable performance. The VSWR remains  $\leq$  1.5:1 at 6000 MHz, ensuring minimal signal reflection and loss.

Compliant...

Read More





#### Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

## RF Connector Interface

RF Interface	Body Shape	Mounting
N Female	Straight	Free Hanging

# RF Specification


Start Frequency:	0 GHz	Input Impedance:	50
Stop Frequency:	6 GHz	Insulation Resistance:	≥ 5000 mΩ
		RF Operating Voltage:	≤ 1000 Vrms

### **VSWR** Measurement

Frequency	VSWR
6000 MHz	≤ 1.5:1

# **Physical Specification**

L-400	Conductor Attachment:	Cable, Crimp
Brass	Contact Material:	Brass
Nickel	Contact Plating:	Gold
PTFE / Teflon	Min. Operating Temperature:	-55 °C
20.5 × 13.6	Max. Operating Temperature:	165 °C
RoHS	Mating Cycles:	> 500
	Brass Nickel  PTFE / Teflon  20.5 × 13.6	Brass Contact Material:  Nickel Contact Plating:  PTFE / Teflon Min. Operating Temperature:  20.5 × 13.6 Max. Operating Temperature:



Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

