

PTL-400 Coaxial Cable N Male to N Male 15m

SKU: ACC-PT-00050

MPN: CA-P400-N1N1.15

Barcode: 9337692002021

Description

The PTL-400 Coaxial Cable N Male to N Male, 15m (SKU: ACC-PT-00050) by Powertec is a premium RF cable solution designed for wireless communication systems. With a PTL-400 L-400 class low loss specification, this cable boasts a 10.29 mm outer diameter, supporting frequencies up to 6 GHz. Its construction includes a double shielded outer conductor with aluminium tape and tinned copper braiding, providing exceptional RF shielding exceeding 90 dB. This ensures reliable performance in demanding environments.

The cable features a durable PE jacket, offering a service life exceeding 20 years, and is engineered to endure over 500 mating cycles. Each end of the cable is equipped with an N Male connector, featuring a straight body shape and free hanging mounting style, ensuring secure and stable connections.

Weighing 1550 grams, this 15-metre cable is compliant with ISO 9001 Quality Management and RoHS certifications, guaranteeing high standards in...

[Read More](#)



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

| | | | |
|------------------|-------|-----------------|-------|
| Start Frequency: | 0 GHz | Stop Frequency: | 6 GHz |
|------------------|-------|-----------------|-------|

Physical Specification

| | | | |
|----------------------------|-----------------------------|---------|--------|
| Subtype: | Feeder Cable | Length: | 15 m |
| Mating Cycles: | > 500 | Weight: | 1550 g |
| Compliance/Certifications: | ISO 9001 Quality Management | | |
| RoHS | | | |

RF Connectors

| RF Interface | Body Shape | Mounting |
|--------------|------------|--------------|
| N Male | Straight | Free Hanging |
| N Male | Straight | Free Hanging |

PTL-400

| | | | |
|---------------------------|----------|--------------------------|---------|
| Min. Frequency: | 0 GHz | Max. Frequency: | 6 GHz |
| Impedance: | 50 | Shielding Effectiveness: | > 90 dB |
| Min. Bend Radius Static: | 25.4 mm | Colour: | Black |
| Min. Bend Radius Dynamic: | 101.6 mm | Weight (g/m): | 100 g |

Cable Layers

| Layer | Diameter | Materials |
|-----------------|----------|---|
| Inner Conductor | 2.74 mm | Copper Clad Aluminium (CCA) |
| Dielectric | 7.24 mm | Foamed Polyethylene (EPE) |
| Outer Conductor | 7.39 mm | Aluminium Foil (Bonded) |
| Outer Conductor | 8.13 mm | Tinned Copper Braid (TC), Tinned Copper Clad AlMg |
| Outer Jacket | 10.29 mm | Polyethylene (PE) |

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

