

PTL-400 Coaxial Cable N Male to N Male 10m

SKU: ACC-PT-00068
 MPN: CA-P400-N1N1.10
 Barcode: 9337692002014

Description

The Powertec PTL-400 Coaxial Cable N Male to N Male 10m (SKU: ACC-PT-00068) is a high-performance RF cable ideal for wireless communication systems. Featuring a PTL-400 series design, this low-loss coaxial cable supports frequencies up to 6 GHz, making it suitable for a range of applications from entry-level to intermediate systems. With a 10.29 mm outer diameter, the cable is flexible, utilising a double-layered outer conductor of aluminium tape and tinned copper braiding, delivering exceptional RF shielding exceeding 90 dB.

The cable is encased in a durable PE jacket, ensuring a service life of over 20 years. It withstands over 500 mating cycles, offering reliable long-term performance. Both ends of the 10m cable are equipped with N Male connectors featuring a straight body and free-hanging mounting style, ensuring secure connections.

Weighing 1050 grams, the PTL-400 cable meets ISO 9001 Quality Management and RoHS certifications...

[Read More](#)



RF Specification

Start Frequency:	0 GHz	Stop Frequency:	6 GHz
------------------	-------	-----------------	-------

Physical Specification

Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

Subtype:	Feeder Cable	Length:	10 m
Mating Cycles:	> 500	Weight:	1050 g
Compliance/Certifications:	ISO 9001 Quality Management		
RoHS			

RF Connectors

RF Interface	Body Shape	Mounting
N Male	Straight	Free Hanging
N Male	Straight	Free Hanging

PTL-400

Min. Frequency:	0 GHz	Max. Frequency:	6 GHz
Impedance:	50	Shielding Effectiveness:	> 90 dB
Min. Bend Radius Static:	25.4 mm	Colour:	Black
Min. Bend Radius Dynamic:	101.6 mm	Weight (g/m):	100 g

Cable Layers

Layer	Diameter	Materials
Inner Conductor	2.74 mm	Copper Clad Aluminium (CCA)
Dielectric	7.24 mm	Foamed Polyethylene (EPE)
Outer Conductor	7.39 mm	Aluminium Foil (Bonded)
Outer Conductor	8.13 mm	Tinned Copper Braid (TC), Tinned Copper Clad AlMg
Outer Jacket	10.29 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

