

PTL-400 Coaxial Cable N Male to N Male 20m

SKU: ACC-PT-00071

MPN: CA-P400-N1N1.20

Barcode: 9337692002038

Description

The PTL-400 Coaxial Cable N Male to N Male 20m (SKU: ACC-PT-00071) by Powertec is a high-performance RF cable, ideal for wireless communication systems. Designed as part of the L-400 class, this low-loss coaxial cable features a 10.29 mm outer diameter and supports frequencies up to 6 GHz, making it suitable for entry to intermediate-level applications. Its flexible design utilises a double outer conductor, combining aluminium tape and tinned copper braiding, delivering exceptional RF shielding exceeding 90 dB. The durable PE jacket ensures a service life of over 20 years.

This 20 m cable weighs 2050 grams and is engineered to endure over 500 mating cycles. It operates efficiently across a frequency range from 0 to 6 GHz. Both ends of the cable are equipped with N Male connectors, featuring a straight body shape and free-hanging mounting style, ensuring reliable connectivity.

Compliant with ISO 9001 Quality Management and RoHS standards...

[Read More](#)



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

Start Frequency:	0 GHz	Stop Frequency:	6 GHz
------------------	-------	-----------------	-------

Physical Specification

Subtype:	Feeder Cable	Length:	20 m
Mating Cycles:	> 500	Weight:	2050 g
Compliance/Certifications:	ISO 9001 Quality Management		
RoHS			

RF Connectors

RF Interface

N Male

N Male

Body Shape

Straight

Straight

Mounting

Free Hanging

Free Hanging

PTL-400

Min. Frequency:	0 GHz	Max. Frequency:	6 GHz
Impedance:	50	Shielding Effectiveness:	> 90 dB
Min. Bend Radius Static:	25.4 mm	Colour:	Black
Min. Bend Radius Dynamic:	101.6 mm	Weight (g/m):	100 g

Cable Layers

Layer	Diameter	Materials
Inner Conductor	2.74 mm	Copper Clad Aluminium (CCA)
Dielectric	7.24 mm	Foamed Polyethylene (EPE)
Outer Conductor	7.39 mm	Aluminium Foil (Bonded)
Outer Conductor	8.13 mm	Tinned Copper Braid (TC), Tinned Copper Clad AlMg
Outer Jacket	10.29 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

