

Powertec Wireless Technology ABN: 42 082 948 463 PO Box 1034, Ashmore City Queensland, Australia, 4214 sales@powertec.com.au 1300 769 378

PTL-400 Coaxial Cable N Male to N Male 5m

SKU: ACC-PT-00074 MPN: CA-P400-N1N1.5 Barcode: 9337692002007

Description

The PTL-400 Coaxial Cable N Male to N Male 5m, model number CA-P400-N1N1.5, is a high-performance RF cable developed by Powertec. This PTL-400 series cable, with a 10.29 mm outer diameter, is an L-400 class low loss coaxial cable designed for wireless communication systems operating up to 6 GHz. Its flexible double outer conductor, composed of aluminium tape and tinned copper braiding, ensures exceptional RF shielding exceeding 90 dB. The cable features a durable PE jacket, offering a service life exceeding 20 years, and is designed to withstand over 500 mating cycles.

The 5-metre cable comes with N Male connectors on both ends, each with a straight body and free-hanging mounting style, making it suitable for a variety of applications. Weighing 550 grams, it is easy to handle and install. The cable is ISO 9001 and RoHS certified, ensuring high-quality standards and compliance with environmental regulations.

Powertec, the Australian-based...

Read More





Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

|--|

Physical Specification

Subtype:	Feeder Cable	Length:	5 m
Mating Cycles:	Mating Cycles: > 500 Weight: 550 g		
Compliance/Certifications:	ISO 9001 Quality Management		
RoHS			

RF Connectors

RF Interface	Body Shape	Mounting
N Male	Straight	Free Hanging
N Male	Straight	Free Hanging

PTL-400

Min. Frequency:	0 GHz	Max. Frequency:	6 GHz
Impedance:	50	Shielding Effectiveness:	> 90 dB
Min. Bend Radius Static:	25.4 mm	Colour:	Black
Min. Bend Radius Dynamic:	101.6 mm	Weight (g/m):	100 g

Cable Layers

Inner Conductor 2.74 mm Copper Clad Aluminium (CCA) Dielectric 7.24 mm Foamed Polyethylene (EPE) Outer Conductor 7.39 mm Aluminium Foil (Bonded) Outer Conductor 8.13 mm Tinned Copper Braid (TC), Tinned Copper Clad AlMg Outer lacket 10.29 mm Polyethylene (PE)	Layer	Diameter	Materials
Outer Conductor 7.39 mm Aluminium Foil (Bonded) Outer Conductor 8.13 mm Tinned Copper Braid (TC), Tinned Copper Clad AlMg	Inner Conductor	2.74 mm	Copper Clad Aluminium (CCA)
Outer Conductor 8.13 mm Tinned Copper Braid (TC), Tinned Copper Clad AIMg	Dielectric	7.24 mm	Foamed Polyethylene (EPE)
	Outer Conductor	7.39 mm	Aluminium Foil (Bonded)
Outer lacket 10.29 mm Polyethylene (PF)	Outer Conductor	8.13 mm	Tinned Copper Braid (TC), Tinned Copper Clad AlMg
outer jacket	Outer Jacket	10.29 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

