

L-195 Patch Cable SMA Male to SMA Male, 1m

SKU: ACC-PT-00103

MPN: CA-195-SA1SA1.100

Barcode: 9337692000072

Description

The L-195 Patch Cable, SKU: ACC-PT-00103, by Powertec is a high-performance RF coaxial cable designed for versatile use in HF/UHF/VHF and 4G applications. Featuring SMA Male connectors on both ends, the cable offers a straight body shape and free-hanging mounting style. As part of the PTL-195 series, this low-loss cable measures 1 metre in length with a 4.95 mm outer diameter, providing a superior alternative to the RG-58 cable.

It supports frequencies up to 6 GHz, making it ideal for short-length high-frequency applications. The cable is lightweight at 80 grams and boasts flexibility for easy installation. Engineered for durability, it can endure over 500 mating cycles. The L-195 Patch Cable delivers excellent performance with a VSWR of $\leq 1.4:1$ and insertion loss of 0.75 dB at 3000 MHz, and 1.2 dB at 6000 MHz.

This cable meets ISO 9001 Quality Management and RoHS certifications, ensuring compliance with international standards. As a...

[Read More](#)



Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

RF Specification

Start Frequency: 0 GHz Stop Frequency: 6 GHz

VSWR Measurement

Frequency	VSWR	Insertion Loss
3000 MHz	$\leq 1.4:1$	0.75 dB
6000 MHz	$\leq 1.4:1$	1.2 dB

Physical Specification

Subtype: Patch Cable Length: 1 m

Mating Cycles: > 500 Weight: 80 g

Compliance/Certifications: ISO 9001 Quality Management

RoHS

RF Connectors

RF Interface

SMA Male

SMA Male

Body Shape

Straight


Straight

Mounting

Free Hanging

Free Hanging

Drawing



PTL-195

Min. Frequency:	0 GHz	Max. Frequency:	6 GHz
Impedance:	50	Shielding Effectiveness:	> 90 dB
Min. Bend Radius Static:	12.7 mm	Colour:	Black
Min. Bend Radius Dynamic:	50.8 mm	Weight (g/m):	30 g

Cable Layers

Layer	Diameter	Materials
Inner Conductor	0.94 mm	Solid Copper
Dielectric	2.97 mm	Foamed Polyethylene (EPE)
Outer Conductor	2.95 mm	Aluminium Foil (Bonded)
Outer Conductor	3.53 mm	Tinned Copper Braid (TC)
Outer Jacket	4.95 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

