

# L-195 Patch Cable N Female to SMA Male 40cm

SKU: ACC-PT-00110

MPN: CA-L19-N2SA1.040

Barcode: 9337692000096

## Description

The L-195 Patch Cable, N Female to SMA Male, 40cm (SKU: ACC-PT-00110), is a high-performance RF coaxial cable from Powertec, part number CA-L19-N2SA1.040. Featuring the PTL-195 series low-loss coaxial design, this cable offers a compact 4.95 mm outer diameter, making it an ideal upgrade from the RG-58 for applications requiring higher performance. Supporting frequencies up to 6 GHz, it is suitable for HF, UHF, VHF, and short-length high-frequency applications such as 4G.

The cable is 0.4 m long and weighs 62 grams, providing flexibility and ease of installation. It is designed to endure over 500 mating cycles, ensuring durability in various settings. The operating frequency range extends from 0 GHz to 6 GHz, with compliance to ISO 9001 and RoHS standards ensuring quality and safety.

Equipped with an N Female connector with a Straight Bulkhead mounting on one end, and an SMA Male connector with a Straight Free Hanging mounting on the other...

[Read More](#)



## Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

# RF Specification

Start Frequency:	0 GHz	Stop Frequency:	6 GHz
------------------	-------	-----------------	-------

VSWR Measurement			
Frequency	VSWR	Insertion Loss	
3000 MHz	≤ 1.4:1	0.3 dB	
6000 MHz	≤ 1.4:1	0.48 dB	

# Physical Specification

Subtype:	Patch Cable	Length:	0.4 m
Mating Cycles:	> 500	Weight:	62 g
Compliance/Certifications:	ISO 9001 Quality Management		
RoHS			

# RF Connectors

## RF Interface

N Female

SMA Male

## Body Shape

Straight


Straight

## Mounting

Bulkhead

Free Hanging

# Drawing



## PTL-195

Min. Frequency:	0 GHz	Max. Frequency:	6 GHz
Impedance:	50	Shielding Effectiveness:	> 90 dB
Min. Bend Radius Static:	12.7 mm	Colour:	Black
Min. Bend Radius Dynamic:	50.8 mm	Weight (g/m):	30 g

## Cable Layers

Layer	Diameter	Materials
Inner Conductor	0.94 mm	Solid Copper
Dielectric	2.97 mm	Foamed Polyethylene (EPE)
Outer Conductor	2.95 mm	Aluminium Foil (Bonded)
Outer Conductor	3.53 mm	Tinned Copper Braid (TC)
Outer Jacket	4.95 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

