

L-195 Patch Cable N Male to SMA Male 75 cm

SKU: ACC-PT-00115

MPN: CA-R58-N1SA1.075

Barcode: 9337692000744

Description



RF Specification

Start Frequency: 0 GHz Stop Frequency: 6 GHz

Physical Specification

Subtype:	Patch Cable	Length:	0.75 m
Mating Cycles:	> 500	Weight:	73 g
Compliance/Certifications:	ISO 9001 Quality Management		
RoHS	'		

RF Connectors

RF Interface	Body Shape	Mounting
N Male	Straight	Free Hanging
SMA Male	Straight	Free Hanging

PTL-195

Min. Frequency:	0 GHz	Max. Frequency:	6 GHz
Impedance:	50	Shielding Effectiveness:	> 90 dB
Min. Bend Radius Static:	12.7 mm	Colour:	Black
Min. Bend Radius Dynamic:	50.8 mm	Weight (g/m):	30 g

Cable Layers

Layer	Diameter	Materials
Inner Conductor	0.94 mm	Solid Copper
Dielectric	2.97 mm	Foamed Polyethylene (EPE)
Outer Conductor	2.95 mm	Aluminium Foil (Bonded)
Outer Conductor	3.53 mm	Tinned Copper Braid (TC)
Outer Jacket	4.95 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

