

PTL-400 Coaxial Cable N Male to N Male 50m

SKU: ACC-PT-00169
 MPN: CA-P400-N1N1.50
 Barcode: 9337692002076

Description

The PTL-400 Coaxial Cable, model ACC-PT-00169, by Powertec, is a high-performance RF cable designed for wireless communication systems. With a 10.29 mm outer diameter, this L-400 class cable supports frequencies up to 6 GHz, making it ideal for entry- to intermediate-level applications. The cable features a double outer conductor—aluminium tape and tinned copper braiding—that provides over 90 dB of RF shielding, ensuring excellent signal integrity. Encased in a durable PE jacket, it promises a service life exceeding 20 years.

This 50 m cable, weighing 5050 g, is equipped with N Male connectors on both ends, offering a straight body shape and free-hanging mounting style. Designed to withstand over 500 mating cycles, it ensures long-term reliability in demanding environments. The PTL-400 is compliant with ISO 9001 Quality Management and RoHS standards, reflecting its commitment to quality and environmental responsibility.

As a product of...

[Read More](#)



RF Specification

Start Frequency: 0 GHz Stop Frequency: 6 GHz

Powertec



Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

Physical Specification

| | | | |
|----------------------------|-----------------------------|---------|--------|
| Subtype: | Feeder Cable | Length: | 50 m |
| Mating Cycles: | > 500 | Weight: | 5050 g |
| Compliance/Certifications: | ISO 9001 Quality Management | | |
| RoHS | | | |

RF Connectors

| RF Interface | Body Shape | Mounting |
|--------------|------------|--------------|
| N Male | Straight | Free Hanging |
| N Male | Straight | Free Hanging |

PTL-400

| | | | |
|---------------------------|----------|--------------------------|---------|
| Min. Frequency: | 0 GHz | Max. Frequency: | 6 GHz |
| Impedance: | 50 | Shielding Effectiveness: | > 90 dB |
| Min. Bend Radius Static: | 25.4 mm | Colour: | Black |
| Min. Bend Radius Dynamic: | 101.6 mm | Weight (g/m): | 100 g |

Cable Layers

| Layer | Diameter | Materials |
|-----------------|----------|---|
| Inner Conductor | 2.74 mm | Copper Clad Aluminium (CCA) |
| Dielectric | 7.24 mm | Foamed Polyethylene (EPE) |
| Outer Conductor | 7.39 mm | Aluminium Foil (Bonded) |
| Outer Conductor | 8.13 mm | Tinned Copper Braid (TC), Tinned Copper Clad AlMg |
| Outer Jacket | 10.29 mm | Polyethylene (PE) |

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

