

Page



Powertec Wireless Technology  
ABN: 42 082 948 463  
PO Box 1034, Ashmore City  
Queensland, Australia, 4214  
sales@powertec.com.au  
1300 769 378

## **RG-402 Patch Cable N Male to SMA Male Low PIM 50cm**

SKU  
ACC-PT-00305  
MPN  
CA-R402-N1SA1.050  
Barcode  
9337692002526

## Description

The RG-402 Patch Cable, featuring N Male to SMA Male connectors and measuring 50 cm, is engineered by Powertec for superior RF performance. Designed with Powertec's PSF-402 Series coaxial cable, this 0.141" semi-flexible cable offers low loss and supports frequencies up to 34 GHz, making it ideal for efficient component interconnection. Its bright blue 4.2 mm outer jacket is not only visually distinctive but also highly durable, preventing solder joint failures and allowing flexibility with bends directly behind the fillet.

This cable boasts nearly 100% RF shielding thanks to its tin-soaked copper braid, and it is hand-formable, making it suitable for microwave-grade applications with mode-free operation up to 34 GHz. The RG-402 is known for its low Passive Intermodulation (PIM) with a 3rd Order PIM rating of -120 dBc, ensuring optimal signal integrity. It accommodates over 500 mating cycles, ensuring long-term reliability.

Operating...

[Read More](#)





## Powertec

Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems developer. Supporting over 1500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...

## RF Specification

Start Frequency

0 GHz

PIM, 3rd Order

-120 dBc

Stop Frequency

6 GHz

VSWR Measurement

### **Frequency VSWR**

3000 MHz  $\leq 1.2:1$

6000 MHz  $\leq 1.5:1$

## Physical Specification

Subtype

[Patch Cable](#)

Mating Cycles

> 500

Compliance/Certifications

## ISO 9001 Quality Management

,

### RoHS

Length

0.5 m

Weight

63 g


## **RF Connectors**

### **RF Interface Body Shape Mounting**

N Male      Straight      Free Hanging

SMA Male      Straight      Free Hanging

Drawing



### **PSF-402**

Min. Frequency

0 GHz

Impedance

50  $\Omega$

Min. Bend Radius Static

8 mm

Min. Bend Radius Dynamic

40 mm

Max. Frequency

34 GHz

Shielding Effectiveness

> 110 dB

Colour

Blue

## Cable Layers

Layer	Diameter	Materials
Inner Conductor	0.93 mm	<a href="#">Silver Plated Copper (SC)</a>
Dielectric	3.00 mm	<a href="#">PTFE / Teflon</a>
Outer Conductor	3.52 mm	<a href="#">Tin Soaked Copper Braid</a>
Outer Jacket	4.20 mm	<a href="#">Polyolefin LSZH</a>

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

