

PTL-240 Coaxial Cable N Male to N Male 3m

SKU: ACC-PT-00349
 MPN: CA-P240-N1N1.3
 Barcode: 9337692002472

Description



RF Specification

Start Frequency:	0 GHz	Stop Frequency:	6 GHz
------------------	-------	-----------------	-------

Physical Specification

Subtype:	Jumper Cable Powertec	Length:	3 m
Mating Pins:	> 500	Weight:	200 g
Compliance/Certifications:	ISO 9001 Quality Management Powertec is a wireless technology manufacturer and systems integrator based in Australia. Operating since 1995, Powertec has grown to become the leading wireless technology distributor in its region, and a leading Infratech systems partner. With over 500 partners the company provides procurement, design, project management, and support services across Australia, New Zealand, Pacific ...		
RoHS			

RF Connectors

RF Interface

Body Shape

Mounting

N Male

Straight

Free Hanging

N Male

Straight

Free Hanging

PTL-240

Min. Frequency:	0 GHz	Max. Frequency:	6 GHz
Impedance:	50	Shielding Effectiveness:	> 90 dB
Min. Bend Radius Static:	19.1 mm	Colour:	Black
Min. Bend Radius Dynamic:	63.5 mm	Weight (g/m):	50 g

Cable Layers

Layer	Diameter	Materials
Inner Conductor	1.42 mm	Solid Copper
Dielectric	3.81 mm	Foamed Polyethylene (EPE)
Outer Conductor	3.94 mm	Aluminium Foil
Outer Conductor	4.52 mm	Tinned Copper Braid (TC)
Outer Jacket	6.10 mm	Polyethylene (PE)

Disclaimer: Although care has been taken to ensure the accuracy, completeness and reliability of the information provided, Powertec assumes no responsibility therefore. The user of the information agrees that the information is subject to change without notice. Powertec assumes no responsibility for the consequences of use of such information, nor for any infringement of third party intellectual property rights which may result from its use. IN NO EVENT SHALL POWERTEC BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, OR INCIDENTAL DAMAGE RESULTING FROM, ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE INFORMATION.

